



The Ontario Gazette La Gazette de l'Ontario

Vol. 147-02
Saturday, 11 January 2014

Toronto

ISSN 00302937
Le samedi 11 janvier 2014

Government Notices Respecting Corporations Avis du gouvernement relatifs aux compagnies

Notice of Default in Complying with the Corporations Tax Act Avis de non-observation de la Loi sur l'imposition des sociétés

The Director has been notified by the Minister of Finance that the following corporations are in default in complying with the *Corporations Tax Act*.

NOTICE IS HEREBY GIVEN under subsection 241(1) of the *Business Corporations Act*, that unless the corporations listed hereunder comply with the requirements of the *Corporations Tax Act* within 90 days of this notice, orders will be made dissolving the defaulting corporations. All enquiries concerning this notice are to be directed to Ministry of Finance, Corporations Tax, 33 King Street West, Oshawa, Ontario L1H 8H6.

Le ministre des Finances a informé le directeur que les sociétés suivantes n'avaient pas respecté la *Loi sur l'imposition des sociétés*.

AVIS EST DONNÉ PAR LA PRÉSENTE que, conformément au paragraphe 241(1) de la *Loi sur les sociétés par actions*, si les sociétés citées ci-dessous ne se conforment pas aux prescriptions énoncées par la *Loi sur l'imposition des sociétés* dans un délai de 90 jours suivant la réception du présent avis, lesdites sociétés se verront dissoutes par décision. Pour tout renseignement relatif au présent avis, veuillez vous adresser à l'Imposition des sociétés, ministère des Finances, 33, rue King ouest, Oshawa ON L1H 8H6.

Name of Corporation: Dénomination sociale de la société:	Ontario Corporation Number Numéro de la société en Ontario
2014-01-11	
ADELAIDE RESTAURANT GROUP INC.	001104812
ANGELINI ITAL CUISINE LTD.	000795824
C.T. SOIL & MATERIALS ENGINEERING INC.	000997149
COAL LTD.	001590103
COMMERCIAL CREDIT INFORMATION INC.	001111272
DE MELO FOODS LIMITED	000771450
DECKER MEDICAL PUBLISHING INC.	000740972
DIRECT ACCESS INFORMATION SYSTEMS INC.	000730676
DON MAC VIDEO INC	000800916
DONWAY PAPER CONVERTING CORPORATION	000394188

Name of Corporation: Dénomination sociale de la société:	Ontario Corporation Number Numéro de la société en Ontario
DREAMSCAPE INC.	001336455
DRILL CORE COMPANY LIMITED	000313220
DUNADAM DEVELOPMENTS INC.	001021428
EDINBURGH REAL ESTATE LTD.	000665036
EHT CONTRACTING LTD.	001567955
ESDEN DISTRIBUTION INC.	001104804
EUROTECH DIE CASTING INC.	000854908
EX-L MARKETING INC.	001540126
F & M HOME IMPROVEMENTS LTD.	000814184
FARTHAN CONTRACTORS LIMITED	000270856
FINANCIAL FREEDOM RESOURCE MANAGEMENT GROUP INC.	001045664
FITNESS HORIZON HEALTH CLUB LTD.	001417786
FLAT GLASS INTERNATIONAL INC.	000543248
FORTUNE REALTY INC.	000653920
FRESWOOD CUSTOM CABINETS INC.	001243159
GIANT BAY REALTY LTD.	000917344
GLOBE ENVIRONMENTAL SERVICES INC.	001701882
GOLD MEDAL LEGAL & ASSOCIATES INC.	002105601
GREATER CANADA INVESTMENT CORPORATION	000911012
HORSESHOE VALLEY CONSTRUCTION LTD.	000977480
HUBBARD-WILSON ASSOCIATES INC.	000870108
I. M. E. T. TECHNOLOGIES INC.	000347272
INDEPENDENT ROOFING SERVICES INC	000804624
J. C. P. CHILDREN DAY CARE SERVICE LIMITED	000814968
JBD RENOVATIONS LTD.	002099884
JEFFREY MUFFLERS LIMITED	000137325
KARAOUZAS HOLDINGS LTD.	000395256
KYMBO CANADA INC.	001100656
LAKESHORE FRAMING LTD.	002072995
LAKESHORE PRODUCTIONS LTD.	001036308
LASER TECH AUTO COLLISION & REPAIR INC.	001024796
MACANDREW RED LAKE GOLD MINES, LIMITED	000039796
MADONNA BAGS LTD.	000655276
MARKIMAT HOLDINGS INC.	000531756
MAXIMUM SALES CORPORATION	000915624
MCBURNIE TRANSPORT LIMITED	001622175
MOTION SUPPLY INC.	001099616
NEW BAIDWAN TRANS INC.	002107273

Name of Corporation: Dénomination sociale de la société:	Ontario Corporation Number Numéro de la société en Ontario
NORTHFIELD KITCHEN INC.	002012453
OUTBACK STEAKHOUSES INC.	001014556
PERLY INTERNATIONAL INC.	001228886
POOL & SPA HOUSE LTD.	001085436
PRATT & MURRAY REALTY INC.	000873116
PRIM CONTRACTING INC.	001107404
PRINCESS BRIDAL DESIGN LTD.	000857916
PROPERTY MASTERS INC.	000902968
PYRAMID CONSTRUCTION LIMITED	000471228
Q QUEST ASSETS LIMITED. COM	001346644
QUALITY SYSTEMS TECHNOLOGIES CORPORATION	001621967
RADAR STUDIOS INC.	001385307
ROBERT AVON HOLDINGS INC.	000576512
ROYAL PALLETS INC.	002119693
SAFECOM-UEP LIMITED	000996512
SCARLETT MEDIA INC.	001474315
SCOTT MORREAU INCORPORATED	001002084
SHANE MURPHY'S ONE STOP INC.	001277911
SHIU GEOMATICS LIMITED	002016094
SIDNEY L. MORRIS SECURITIES INC.	000630216
STARPLEX ENTERTAINMENT INC.	001647083
THE UNIQUE POND COMPANY INC.	001655050
TIM-DAN HOLDINGS INC.	000552068
TOP GUARDS INC.	000657068
TORGLOBAL TRANSPORTATION SERVICES INC.	001070030
TOSHOF RENOVATION AND DESIGN INC.	000771412
TRAILMOBILE CANADA LIMITED	001216081
TWOSOME INCORPORATED	002017597
VARKOMBI INTERNATIONAL INCORPORATED	002105193
VITALEY FURNITURE LTD.	000947360
WHEEL CARE PLUS INC.	001089864
WHEEL 'N DEAL, INC.	000367720
YAMAMOTO HYPERTHERMIC ONCO-TECH INC.	000862032
ZANSHIN STUDIES INC.	000805828
1000175 ONTARIO INC.	001000175
1004356 ONTARIO INC.,	001004356
1015452 ONTARIO INC.	001015452
1020368 ONTARIO LIMITED	001020368
1022084 ONTARIO INC.	001022084
1036360 ONTARIO INC.	001036360
1037624 ONTARIO INC.	001037624
1039876 ONTARIO LIMITED	001039876
1053260 ONTARIO INC.	001053260
1053384 ONTARIO INC.	001053384
1071580 ONTARIO INC.	001071580
1076872 ONTARIO LTD.	001076872
1078512 ONTARIO LTD.	001078512
1082940 ONTARIO LIMITED	001082940
1109212 ONTARIO INC.	001109212
1110444 ONTARIO LIMITED	001110444
1211932 ONTARIO INC.	001211932
1217269 ONTARIO INC.	001217269
1337435 ONTARIO LIMITED	001337435
1499063 ONTARIO LIMITED	001499063
1522485 ONTARIO LIMITED	001522485
1564357 ONTARIO LIMITED	001564357
1635767 ONTARIO LIMITED	001635767
1704288 ONTARIO INC.	001704288
2113717 ONTARIO INC.	002113717
303484 ONTARIO INC.	000303484
563512 ONTARIO LIMITED	000563512
628508 ONTARIO LIMITED	000628508
658156 ONTARIO INC.	000658156
690724 ONTARIO INC.	000690724
691532 ONTARIO INC.	000691532

Name of Corporation: Dénomination sociale de la société:	Ontario Corporation Number Numéro de la société en Ontario
707432 ONTARIO LIMITED	000707432
801046 ONTARIO INC	000801046
810328 ONTARIO INC.	000810328
825472 ONTARIO LIMITED	000825472
926348 ONTARIO INC.	000926348
957396 ONTARIO LIMITED	000957396
988140 ONTARIO INC	000988140

WILLIAM D. SNELL
Director, Ministry of Government Services
Directeur, Ministère des Services
gouvernementaux

(147-G008)

Cancellation of Certificate of Incorporation (Corporations Tax Act Defaulters) Annulation de certificat de constitution (Non-observation de la Loi sur l'imposition des sociétés)

NOTICE IS HEREBY GIVEN that, under subsection 241(4) of the *Business Corporations Act*, the Certificate of Incorporation of the corporations named hereunder have been cancelled by an Order for default in complying with the provisions of the *Corporations Tax Act*, and the said corporations have been dissolved on that date.

AVIS EST DONNÉ PAR LA PRÉSENTE que, conformément au paragraphe 241(4) de la *Loi sur les sociétés par actions*, le certificat de constitution de la société sous-nommé a été annulé par Ordre pour non-observation des dispositions de la *Loi sur l'imposition des sociétés* et que la dissolution de la société concernée prend effet à la date susmentionnée.

Name of Corporation: Dénomination sociale de la société:	Ontario Corporation Number Numéro de la société en Ontario
2013-12-16	
ABEERA LTD.	001694452
AJAR LOGISTICS INC.	001648460
ALBION HILLS INDUSTRIES LTD.	000501506
ARCH PLUS BUILDING INC.	002026348
AVAIL SOLUTIONS INC.	002105913
BON APPAREL LTD.	001708514
BULKEX LIMITED	002098339
CAFE GROTO INC.	001274368
CANADIAN SMALL CAP RESOURCE FUND 2006 NO. 2 MANAGEMENT LTD.	002109441
CARFOREX CORPORATION	002104282
CHILDREN'S CORNER DAY NURSERY INC.	000871198
CS MED LABELS INC.	002108485
D.T.E. ELECTRIC INC.	001215735
DEAD LAND NORTH INC.	002052194
DICK ROWE CARTAGE LTD.	001224753
EAGLE SUMMIT PET FOODS INC.	002006840
EARTHEN KARMA INC.	002098991
ELINKPAGES INC.	001705320
ENGLISH PRESTIGE HOLDING CORP.	002108166
ERPANDERP CORP.	002111159
FANOUS CATERING AND BAKERY LIMITED.	002104140
FLAGSHIP TRANSPORTATION SERVICES LTD.	001247071
FORCE ENTERPRISES (QUINTE) LTD.	000899832
FUDA HOME IMPROVEMENTS INC.	001426701
FULL-CUP VENDING LTD.	000543492

Name of Corporation: Dénomination sociale de la société:	Ontario Corporation Number Numéro de la société en Ontario
GEMALA INDUSTRIES LIMITED INDUSTRIES	
GEMALA LIMITEE	000850265
GRD ROCK INTERNATIONAL LTD.	002107908
GREAT LAKES RIGGING HOLDINGS INC.	001684413
HOOKS PASTA & SEAFOOD INC.	001081962
HYPER DAWG INC.	001587549
I LOVE RECESS LTD.	001152335
IRWIN NELSON INC.	001220223
JACOB'S HOLD INC.	000775005
JOY PET PRODUCTS INCORPORATED	001612261
KARPREE CORPORATION	002094220
KRATER INTERNATIONAL TRADING INC.	000845698
L. CHEECHUCK TRANSPORTATION INC.	001459756
LEADERSHIP TRUCK LINES INCORPORATED	001723627
LEADS TECHNICAL GROUP, INC.	001317524
MADRAS & HYDERABAD MAHAL RESTAURANT INC.	001693401
MALCOLM TRANSPORT SERVICES INC.	001610924
MCN 2001 INC.	001694181
MEAT PLUS INC.	000946208
MOSYSTEMS INC.	001290814
NATIONS BRIDAL & EVENTS CO. INC.	001695406
NEW WAVE SOLUTIONS INC.	002105965
NEWMAN GOLF ENTERPRISES INC.	001271830
N2 MANAGEMENT INC.	002094852
O.L.P.P. LIMITED	000701453
OBERON INTERACTIVE INC.	000929903
OMEGA FRESH BAKERY LTD.	002111713
P.D.S. MANUFACTURING & ENGINEERING INC.	000953571
PROMINENCE COMMUNICATIONS CORP.	001699317
REFLECTIONS AUTOMOTIVE CENTRE LTD.	001382130
RESERVOIR HOLDINGS INC.	000629504
ROOSMINA T-SHIRTS INC.	001052384
SACH EXPRESS LTD.	001706494
SAI FINANCIAL GROUP OF COMPANIES INC.	002112874
SRI GANESH CONSULTING INC.	001445699
STONE MOTORS INC.	001480392
TOLL STEEL INDUSTRIES LTD.	001097523
TOOT A LOOT LTD.	002111811
TORE TRUCKING INC.	002105171
TRIPPA BIANCA LTD.	001706004
TRIPPLE R FASHIONS & ACCESSORIES INC.	001706406
TROPICAL FLAVA INC.	002104607
TROTTER'S TOWING LTD.	001304627
UGOBIZ INC.	001675476
VAULT NIGHT CLUB INC.	001694032
VIRTUAL 7 MEDIAS INC.	002107372
VIVA BUILDING TECHNOLOGIES INC.	001704466
WOODGOLD CONTRACTING INC.	000944201
YONG CHANG CANADA TRADING CO. LTD.	001034652
ZAMANI DEVELOPMENTS LTD.	001706072
1038288 ONTARIO LTD.	001038288
1089732 ONTARIO INC.	001089732
110 AUTO INC.	001595310
1100740 ONTARIO INC.	001100740
1163110 ONTARIO LIMITED	001163110
1266789 ONTARIO LIMITED	001266789
1270045 ONTARIO INC.	001270045
1336203 ONTARIO INC.	001336203
1393356 ONTARIO LIMITED	001393356
1395372 ONTARIO INC.	001395372
1413815 ONTARIO INC.	001413815
1443562 ONTARIO INC.	001443562
1478263 ONTARIO LIMITED	001478263
1501339 ONTARIO INC.	001501339
1519716 ONTARIO INC.	001519716
1569311 ONTARIO LIMITED	001569311

Name of Corporation: Dénomination sociale de la société:	Ontario Corporation Number Numéro de la société en Ontario
1579991 ONTARIO LTD.	001579991
1584293 ONTARIO INC.	001584293
1585251 ONTARIO INC.	001585251
1678872 ONTARIO INC.	001678872
1694451 ONTARIO INC.	001694451
1698287 ONTARIO INC.	001698287
1699318 ONTARIO INC.	001699318
1699386 ONTARIO LTD.	001699386
1703620 ONTARIO INC.	001703620
1704467 ONTARIO LTD.	001704467
1704525 ONTARIO LTD.	001704525
1705370 ONTARIO INC.	001705370
1719642 ONTARIO INC.	001719642
1979 CAMPUS INC.	000420183
2060438 ONTARIO LTD.	002060438
2065108 ONTARIO INC.	002065108
2107305 ONTARIO CORPORATION	002107305
2107353 ONTARIO LIMITED	002107353
2108628 ONTARIO INC.	002108628
2109462 ONTARIO INC.	002109462
2110173 ONTARIO CORPORATION	002110173
2111043 ONTARIO LIMITED	002111043
2111844 ONTARIO CORPORATION	002111844
2112055 ONTARIO INC.	002112055
2114076 ONTARIO INC.	002114076
2114321 ONTARIO INC.	002114321
392370 ONTARIO LIMITED	000392370
7 FISH N MEAT INC.	002155614
976631 ONTARIO INC.	000976631

WILLIAM D. SNELL
Director, Ministry of Government Services
Directeur, Ministère des Services
gouvernementaux

(147-G009)

Certificate of Dissolution Certificat de dissolution

NOTICE IS HEREBY GIVEN that a certificate of dissolution under the *Business Corporations Act*, has been endorsed. The effective date of dissolution precedes the corporation listings.

AVIS EST DONNÉ PAR LA PRÉSENTE que, conformément à la *Loi sur les sociétés par actions*, un certificat de dissolution a été inscrit pour les compagnies suivantes : la date d'entrée en vigueur précède la liste des compagnies visées.

Name of Corporation: Dénomination sociale de la société:	Ontario Corporation Number Numéro de la société en Ontario
2013-11-26	
AVIACOR INC.	001252436
ELLIE ALTERATION INC.	002217155
FROZCOR INC.	002295347
GIRAFFE CAPITAL MANAGEMENT INC.	002000368
MEDIA GENERATION CORPORATION	001740665
OLIVE TREE ORGANICS INC.	001701817
WAVE TECHNOLOGIES GROUP INC.	002338137
2207518 ONTARIO INC.	002207518
2013-11-28	
1684449 ONTARIO INC.	001684449
2013-11-29	
BUILDING SHELL PROFESSIONALS INC.	001351248

Name of Corporation: Dénomination sociale de la société:	Ontario Corporation Number Numéro de la société en Ontario
CONDO-GARAGE (NANTUCKET) INC.	001712620
DILSHAN INC.	001452990
ELVIN LETCHFORD ADVERTISING INC.	000652908
NEW SPICELAND VIDEO INC.	002123860
SALON EAU INC.	001762593
SIMPLICITY WORKS REALTY CORP.	002252243
SNACK BRANDS INC.	002127444
THE WRAPUP LIMITED	000809360
TOP STARS BAKERY TAKE AWAY CORPORATION	002142891
TOTAL HEALTH PHYSIO CENTRE INC.	002152313
UNICENTRE OTTAWA INC.	000802734
VELAZQUEZ HOLDINGS INC.	001580477
VENDORTWO INC.	002119096
W.Q.T. INC.	001511924
YOUNG VISION PRODUCTIONS INC.	001625255
1067561 ONTARIO INC.	001067561
1131418 ONTARIO LIMITED	001131418
1644331 ONTARIO LIMITED	001644331
1652568 ONTARIO LTD.	001652568
1743532 ONTARIO LIMITED	001743532
1744942 ONTARIO LTD.	001744942
2179047 ONTARIO INC.	002179047
548600 ONTARIO LTD.	000548600
791209 ONTARIO LIMITED	000791209
804812 ONTARIO LIMITED	000804812
972544 ONTARIO INC.	000972544
2013-12-09	
PAGES DESIGN LTD.	000887492
2013-12-12	
1721615 ONTARIO LIMITED	001721615
2013-12-17	
BADHAN TRANSPORTATION INC.	002083035
VANTAGE MECHANICAL INC.	001192065
2013-12-18	
1197669 ONTARIO INC.	001197669
2296854 ONTARIO LIMITED	002296854
2013-12-19	
ACTRONIX ANTRUM INC.	002008854
AESMALL ENTERPRISE INC.	001831253
AQUA PROOFING INC.	002173988
ARMAND COTE PAINTING INC.	000595813
BAY EAST HOLDINGS INC.	000376075
DIANNE DUNN CONSULTING SERVICES INC.	002190347
DIVERSIFIED BETA STRATEGIES LTD.	002264171
EDGEcombe GROUP INC.	001182506
FEINSCAPING LTD.	001315620
FILI OUTSOURCING INC.	002135479
HAROLD HAFNER HOLDINGS LIMITED	001024984
HIGH WELL TRADING LTD.	002227001
LISLE ELECTRIC LIMITED	002015665
QUADCARD ENTERTAINMENT LTD.	001490773
T.D.D. INVESTMENTS LIMITED	000761772
1087246 ONTARIO INC.	001087246
1586572 ONTARIO LIMITED	001586572
1693808 ONTARIO INC.	001693808
1794425 ONTARIO LIMITED	001794425
1805438 ONTARIO INC.	001805438
2013-12-20	
AL-AMIN INVESTMENTS LIMITED	001252560
AUTODIE CORP.	001073332
BOSWELL CHAPMAN PROFESSIONAL CORPORATION	002268338
CREATEING CORP.	002233067
D & T CUSTOM SPRAYING INC.	000712762
JANBEKELO INVESTMENTS LIMITED	000489425
LANGFORD PHARMACY INC.	001340820
LOVEYOU LIVE DIGITAL ARTS INC.	001854494

Name of Corporation: Dénomination sociale de la société:	Ontario Corporation Number Numéro de la société en Ontario
PLASMID BIOCOMMUNICATIONS INC.	001503467
RAZ CONSTRUCTION INC.	001799240
ROZO DOCTORS INC.	002062219
STARTOURS AWESOME VACATIONS INC.	001405339
SUI GENERIS CAPITAL CORP.	002192592
1058571 ONTARIO LTD.	001058571
1445523 ONTARIO INC.	001445523
1594677 ONTARIO LIMITED	001594677
1782302 ONTARIO INC.	001782302
1867228 ONTARIO INC.	001867228
2137046 ONTARIO LTD.	002137046
2387747 ONTARIO INC.	002387747
665322 ONTARIO LIMITED	000665322
2013-12-23	
APPLIANCE CANADA SALES LTD.	001117853
MEDIQUOTE INC.	001405584
SARGOR INVESTMENTS LTD.	002176101
2118152 ONTARIO INC.	002118152
2236744 ONTARIO INC.	002236744
998780 ONTARIO LTD.	000998780
2013-12-24	
NEL ESTATES LTD.	000291607

WILLIAM D. SNELL
Director, Ministry of Government Services
Directeur, Ministère des Services
gouvernementaux

(147-G010)

Erratum Notice Avis d'erreur

ONTARIO CORPORATION NUMBER 590289

Vide Ontario Gazette, Vol. 146-29 dated July 20, 2013

NOTICE IS HEREBY GIVEN that the notice issued under section 241(4) of the Business Corporations Act set out in the July 20, 2013 issue of the Ontario Gazette with respect to 590289 Ontario Limited, was issued in error and is null and void.

Cf. Gazette de l'Ontario, Vol. 146-29 datée du 20 juillet 2013

PAR LA PRÉSENTE, nous vous informons que l'avis émis en vertu de l'article 241(4) de la Loi sur les sociétés par actions et énoncé dans la Gazette de l'Ontario du 20 juillet 2013 relativement à 590289 Ontario Limited, a été délivré par erreur et qu'il est nul et sans effet.

WILLIAM D. SNELL
Director/Directeur

(147-G011)

Notice of Determination of Residual Stranded Debt for March 31, 2013, under O. Reg. 89/12

NOTICE IS HEREBY GIVEN by the Minister of Finance in accordance with subsection 3(1) of Ontario Regulation 89/12 made pursuant to the Electricity Act, 1998, on the amount of the residual stranded debt for the fiscal year ending March 31, 2013. The Minister of Finance has determined the residual stranded debt to be \$3.9 billion as at March 31, 2013.

Avis de détermination du reliquat de la dette insurmontable en date du 31 mars 2013, en vertu du Règl. de l'Ont. 89/12

AVIS EST PAR LES PRÉSENTES DONNÉ par le ministre des Finances conformément au paragraphe 3(1) du Règlement de l'Ontario 89/12 fait en vertu de la Loi de 1998 sur l'électricité concernant le montant du reliquat de la dette insurmontable pour l'exercice se terminant le 31 mars 2013. Le ministre des Finances a établi le reliquat de la dette insurmontable à 3,9 milliards de dollars en date du 31 mars 2013.

(147-G012)

Applications to Provincial Parliament — Private Bills Demandes au Parlement provincial — Projets de loi d'intérêt privé

PUBLIC NOTICE

The rules of procedure and the fees and costs related to applications for Private Bills are set out in the Standing Orders of the Legislative Assembly's Internet site at <http://www.ontla.on.ca> or from:

Procedural Services Branch
Room 1405, Whitney Block, Queen's Park
Toronto, Ontario M7A 1A2
Telephone: 416/325-3500 (Collect calls will be accepted)

Applicants should note that consideration of applications for Private Bills that are received after the first day of September in any calendar year may be postponed until the first regular Session in the next following calendar year.

DEBORAH DELLER,
Clerk of the Legislative Assembly.

(8699) T.F.N

Applications to Provincial Parliament Demandes au Parlement provincial

NOTICE IS HEREBY GIVEN that on behalf of Vincent Muia application will be made to the Legislative Assembly of the Province of Ontario for an act to revive 394557 Ontario Limited.

The application will be considered by the Standing Committee on Regulations and Private Bills. Any person who has an interest in the application and who wishes to make submissions, for or against the application, to the Standing Committee on Regulations and Private Bills should notify, in writing, the Clerk of the Legislative Assembly, Legislative Building, Queen's Park, Toronto, Ontario, M7A 1A2.

Dated: Toronto This: 9 day of: December 2013

VINCENT MUIA, C.A.

(146-P426) 51, 52, 01, 02

NOTICE IS HEREBY GIVEN that on behalf of Daniel Vu, application will be made to the Legislative Assembly of the Province of Ontario for an Act to revive 1884521 Ontario Limited. The application will be considered by the Standing Committee on Regulations and Private Bills. Any person who has an interest in the application and who wishes to make submissions, for or against the application, to the Standing Committee on Regulations and Private Bills should notify, in writing, the Clerk of the Legislative Assembly, Legislative Building, Queen's Park, Toronto, Ontario, M7A 1A2.

Dated at Toronto, this 19th day of December, 2013.

AILA MAKOOLOO
Makooli Prekupec LLP
300-25 Sheppard Avenue West
Toronto Ontario M2N 6S6
T: 416-848-9815
F: 416-628-5691
Solicitor for the Applicant

(147-P001) 01, 02, 03, 04

Sale of Land for Tax Arrears By Public Tender Ventes de terrains par appel d'offres pour arriéré d'impôt

FORM 6

MUNICIPAL ACT, 2001

SALE OF LAND BY PUBLIC TENDER

THE CORPORATION OF THE TOWN OF BLIND RIVER

TAKE NOTICE that tenders are invited for the purchase of the land(s) described below and will be received until 3:00 p.m. local time on February 19, 2014, at the Town Hall, 11 Hudson Street, P.O. Box 640, Blind River, ON P0R 1B0.

The tenders will then be opened in public on the same day as soon as possible after 3:00 p.m. at the Town Hall, 11 Hudson Street, Blind River.

Description of Land(s):

ROLL NO. 57 38 000 002 13500 0000, PIN 31429-0267 LT, LT D PL 487;
BLIND RIVER, FILE AABR12-002-TT

Minimum Tender Amount:

\$8,536.87

ROLL NO. 57 38 000 004 13900 0000, 9 WEST ST, PIN 31430-0854 LT, LT 45 PL 2713 EXCEPT T24115; S/T T246346; BLIND RIVER, FILE AABR12-003-TT

Minimum Tender Amount: \$13,655.79

ROLL NO. 57 38 000 005 17801 0000, 146 FOREST AVE, PIN 31430-0311 LT, PT LT 5 RANGE B COBDEN PT 1 1R6582 & PT 1 1R5250; BLIND RIVER, FILE AABR12-004-TT

Minimum Tender Amount: \$47,439.98

ROLL NO. 57 38 000 006 12600 0000, 36 CENTRE AVE, PIN 31430-0641 LT, PT LT 111 PL 180 COBDEN AS IN T439650; BLIND RIVER, FILE AABR12-005-TT

Minimum Tender Amount: \$14,091.27

ROLL NO. 57 38 000 006 16500 0000, PIN 31430-0599 LT, LT 75-80 PL 180 COBDEN; BLIND RIVER, FILE AABR12-007-TT

Minimum Tender Amount: \$55,117.66

ROLL NO. 57 38 000 007 04800 0000, PIN 31427-0331 LT, PCL 7464 SEC AES SRO; BLK 39 PL M395 STRIKER; BLIND RIVER, FILE AABR12-009-TT

Minimum Tender Amount: \$4,662.45

ROLL NO. 57 38 000 008 00300 0000, 156 COLONIZATION RD, PIN 31430-0227 LT, PT MILL BLK A COBDEN PT 1 & 2 1R3040 SRO; BLIND RIVER, FILE AABR12-010-TT

Minimum Tender Amount: \$27,463.26

ROLL NO. 57 38 000 008 01713 0000, 23 SCHURM AVE, PIN 31430-0027 LT, PCL 27-1 SEC 1M433 SRO; LT 27 PL 1M433 COBDEN RESERVING THE ROW OF THE CANADIAN PACIFIC RAILWAY; BLIND RIVER, FILE AABR12-011-TT

Minimum Tender Amount: \$6,404.79

ROLL NO. 57 38 000 008 01714 0000, 25 SCHURM AVE, PIN 31430-0028 LT, PCL 28-1 SEC 1M433 SRO; LT 28 PL 1M433 COBDEN RESERVING THE ROW OF THE CANADIAN PACIFIC RAILWAY; BLIND RIVER, FILE AABR12-012-TT

Minimum Tender Amount: \$6,258.20

ROLL NO. 57 38 000 008 13800 0000, 3 DIAMOND AVE, PIN 31430-0188 LT, LT 52-53 PL 2547; BLIND RIVER, FILE AABR12-014-TT

Minimum Tender Amount: \$7,572.16

ROLL NO. 57 38 000 014 07300 0000, 117 ROBB RD, PIN 31426-0046 LT, PCL 5623 SEC AES; LT 12 PL M239 STRIKER (JUDGES PL) T/W BLK C PL M239 AS IN LT51315; BLIND RIVER, FILE AABR12-017-TT

Minimum Tender Amount: \$28,261.81

ROLL NO. 57 38 000 014 16000 0000, 5 BIRCHWOOD CIR, PIN 31423-0243 LT, BLK A PL H540 S/T T174149; BLIND RIVER, FILE AABR12-018-TT

Minimum Tender Amount: \$14,659.06

ROLL NO. 57 38 000 016 13902 0000, PIN 31424-0026 LT, PCL 9802 SEC AES; PT LT 8 CON 5 STRIKER PT 1-3 1R8324; BLIND RIVER, FILE AABR12-020-TT

Minimum Tender Amount: \$10,027.57

ROLL NO. 57 38 000 018 02500 0000, PIN 31432-0086 LT, PCL 7653 SEC ACS; PT LT 3 CON 6 COBDEN (CL3682), PT 1 1R5729; BLIND RIVER – **AND** – PIN 31432-0197 LT, PCL 3114 SEC ACS; PT LT 3 CON 6 COBDEN BEING SUMMER RESORT LOCATION CK296 AS IN A8899, EXCEPT PT 8 1R4941; BLIND RIVER, FILE AABR12-021-TT

Minimum Tender Amount: \$20,439.00

ROLL NO. 57 38 000 018 14200 0000, PIN 31431-0079 LT, E 1/2 OF N 1/2 LT 11 CON 3 COBDEN; BLIND RIVER, FILE AABR12-022-TT

Minimum Tender Amount: \$12,975.65

ROLL NO. 57 38 000 018 27800 0000, 26198 17 HWY, PIN 31432-0392 LT, PT SURRENDERED LANDS OF MISSISSAGI INDIAN RESERVE COBDEN AS IN T223769 T/W T223769; BLIND RIVER, FILE AABR12-025-TT

Minimum Tender Amount: \$9,753.15

Tenders must be submitted in the prescribed form and must be accompanied by a deposit in the form of a money order or of a bank draft or cheque certified by a bank or trust corporation payable to the municipality (or board) and representing at least 20 per cent of the tender amount.

Except as follows, the municipality makes no representation regarding the title to, existing interests in favour of the Crown, environmental concerns or any other matters relating to the land(s) to be sold. Any existing Federal or Provincial Crown liens or executions will remain on title and may become the responsibility of the potential purchaser. Responsibility for ascertaining these matters rests with the potential purchasers.

This sale is governed by the *Municipal Act, 2001* and the Municipal Tax Sales Rules made under that Act. The successful purchaser will be required to pay the amount tendered plus accumulated taxes and the relevant land transfer tax.

The municipality has no obligation to provide vacant possession to the successful purchaser.

Note: H.S.T. may be payable by successful purchaser.

For further information regarding this sale and a copy of the prescribed form of tender contact:

www.Tri-Target.com

or if no internet access available, contact:

MR. GERARD RAINVILLE,
Treasurer
The Corporation of the Town of Blind River
11 Hudson Street, P.O. Box 640
Blind River, ON P0R 1B0
(705) 356-2251 Ext. 207
www.blindriver.com

(147-P005)

MUNICIPAL ACT, 2001

SALE OF LAND BY PUBLIC TENDER

THE CORPORATION OF THE TOWNSHIP OF MADOC

TAKE NOTICE that tenders are invited for the purchase of the land(s) described below and will be received until 3:00 p.m. local time Wednesday, **February 26, 2014** at the Madoc Township Municipal Office, 15651 Highway 62 Madoc, ON K0K 2K0 or by mail to Madoc Township P.O. Box 503 Madoc, ON K0K 2K0. The tenders will then be opened in public on the same day as soon as possible after 3:00 p.m. at the Municipal Office.

Description of Land(s):

Roll No. 12 36 000 010 02300 0000; PIN 40186-0116(LT); Part Lot 6 Concession 7, as in QR308994 Description may not be acceptable in future; S/T Execution 99-0000755 If Enforceable, Madoc, County of Hastings, 33 Tannery Rd.

Minimum Tender Amount: \$3,314.17

Roll No. 12 36 000 020 33700 0000; PIN 40214-0168(LT); Part Lot 28 Concession 6, as in QR80355, Madoc, County of Hastings.

Minimum Tender Amount: \$3,974.63

Roll No. 12 36 000 025 04680 0000; PIN 40182-0075(LT); Part Lot 4 Concession 2 21R13024 Parts 3 & 4 T/W QR5603131, QR560314, S/T MG3143, Madoc, County of Hastings; 104971 Highway 7.

Minimum Tender Amount: \$21,111.31

Tenders must be submitted in the prescribed form and must be accompanied by a deposit in the form of a money order or of a bank draft or cheque certified by a bank or trust corporation payable to the municipality and representing at least **20 per cent** of the tender amount.

Except as follows, the municipality makes no representation regarding the title to or any other matters relating to the land to be sold. Responsibility for ascertaining these matters rests with the potential purchasers.

This sale is governed by the *Municipal Act, 2001* and the Municipal Tax Sales Rules made under that Act. The successful purchaser will be required to pay the amount tendered plus accumulated taxes, the relevant land transfer tax, and Harmonized Sales Tax, if applicable.

The municipality has no obligation to provide vacant possession to the successful purchaser.

For further information regarding this sale and a copy of the prescribed form of tender contact:

CHRISTINE MITCHELL
Treasurer/Tax Collector
The Corporation of the Township of Madoc
15651 Highway 62 PO Box 503
Madoc, ON K0K 2K0
(613) 473-2677 Ext. 201
www.madoc.ca
tax@madoc.ca

(147-P006)

MUNICIPAL ACT, 2001

SALE OF LAND BY PUBLIC TENDER

THE CORPORATION OF THE TOWNSHIP OF CONMEE

TAKE NOTICE that tenders are invited for the purchase of the land described below and will be received until 3:00 p.m. local time on February 12, 2014, at the Township of Conmee Municipal Office, 19 Holland Rd. West, Kakabeka Falls Ontario.

The tenders will then be opened in public on the same day as soon as possible after 3:00 p.m. at the Township of Conmee Municipal Office, 19 Holland Rd. West, Kakabeka Falls.

Description of Land(s):

Roll No. 58 19 000 000 23600 0000; PIN 62303-0124(LT); Parcel 2390 Section DFWF; Part N 1/2 Lot 1 Concession 5 Conmee as in LEW4727 except LEW22196 & Unit 1 D48; Conmee; File No. 12-01

Minimum Tender Amount: \$8,702.29

Tenders must be submitted in the prescribed form and must be accompanied by a deposit in the form of a money order or of a bank draft or cheque certified by a bank or trust corporation payable to the municipality and representing at least 20 per cent of the tender amount.

Except as follows, the municipality makes no representation regarding the title to or any other matters relating to the land to be sold. Responsibility for ascertaining these matters rests with the potential purchasers.

This sale is governed by the *Municipal Act, 2001* and the Municipal Tax Sales Rules made under that Act. The successful purchaser will be required to pay the amount tendered plus accumulated taxes, HST if applicable and the relevant land transfer tax.

The municipality has no obligation to provide vacant possession to the successful purchaser.

For further information regarding this sale and a copy of the prescribed form of tender, visit:

www.OntarioTaxSales.ca

or if no internet access available, contact:

LAURA BRUNI
Treasurer-Deputy Clerk
The Corporation of the Township of Conmee
19 Holland Rd. West
RR #1
Kakabeka Falls Ontario P0T 1W0
(807) 475-5229
conmeelaura@tbaytel.net

(147-P007)

This page intentionally left blank
Cette page est volontairement laissée en blanc

**Publications under Part III (Regulations) of the Legislation Act, 2006
Règlements publiés en application de la partie III (Règlements)
de la Loi de 2006 sur la législation**

2014—01—11

ONTARIO REGULATION 366/13

made under the

DEVELOPMENT CORPORATIONS ACT

Made: November 27, 2013

Filed: December 23, 2013

Published on e-Laws: December 23, 2013

Printed in *The Ontario Gazette*: January 11, 2014

Amending O. Reg. 43/02
(EHEALTH ONTARIO)

1. Section 18 of Ontario Regulation 43/02 is amended by striking out “December 31, 2013” at the end and substituting “December 31, 2014”.

Commencement

2. This Regulation comes into force on the day it is filed.

2/14

ONTARIO REGULATION 367/13

made under the

PERSONAL HEALTH INFORMATION PROTECTION ACT, 2004

Made: November 27, 2013
Filed: December 23, 2013
Published on e-Laws: December 23, 2013
Printed in *The Ontario Gazette*: January 11, 2014

Amending O. Reg. 331/11, which amends O. Reg. 329/04
(GENERAL)

1. Subsection 3 (2) of Ontario Regulation 331/11 is amended by striking out “December 31, 2013” at the end and substituting “December 31, 2014”.

Commencement

2. This Regulation comes into force on the day it is filed.

2/14

RÈGLEMENT DE L'ONTARIO 367/13

pris en vertu de la

LOI DE 2004 SUR LA PROTECTION DES RENSEIGNEMENTS PERSONNELS SUR LA SANTÉ

pris le 27 novembre 2013
déposé le 23 décembre 2013
publié sur le site Lois-en-ligne le 23 décembre 2013
imprimé dans la *Gazette de l'Ontario* le 11 janvier 2014

modifiant le Règl. de l'Ont. 331/11, qui modifie le Règl. de l'Ont. 329/04
(DISPOSITIONS GÉNÉRALES)

1. Le paragraphe 3 (2) du Règlement de l'Ontario 331/11 est modifié par remplacement de «31 décembre 2013» par «31 décembre 2014».

Entrée en vigueur

2. Le présent règlement entre en vigueur le jour de son dépôt.

2/14

ONTARIO REGULATION 368/13

made under the

BUILDING CODE ACT, 1992

Made: December 11, 2013

Filed: December 27, 2013

Published on e-Laws: December 27, 2013

Printed in *The Ontario Gazette*: January 11, 2014Amending O. Reg. 332/12
(BUILDING CODE)**1. Clause 1.4.1.2.(1)(c) of Division A of Ontario Regulation 332/12 is amended by adding the following definitions:***Adaptable seating* means a fixed seat or seats designed to facilitate a side transfer from a wheelchair.*Mobility assistive device* means a mobility assistive device as defined in section 2 of Ontario Regulation 191/11 (Integrated Accessibility Standards) made under the *Accessibility for Ontarians with Disabilities Act, 2005*.**2. Table 1.3.1.2. of Division B of the Regulation is amended by adding the following Items:**

323.1	ISO	23599: 2012	Assistive Products for Blind and Vision-Impaired Persons – Tactile Walking Surface Indicators	3.8.3.18.(1)
.				
348.1	NFPA	72-2013	National Fire Alarm and Signaling Code	3.2.4.22.(13)
				9.10.19.1.(2)
				9.10.19.3.(3)

3. Sentence 3.2.4.19.(4) of Division B of the Regulation is revoked and the following substituted:

(4) Except as permitted by Sentence (6), visual signal devices shall be installed in addition to audible signal devices,

- (a) in a *building* or portion of a *building* intended for use primarily by persons with hearing impairment,
- (b) in a *public corridor* serving a Group A, B, C, D or E *occupancy*,
- (c) in a corridor used by the public and in a *floor area* or part of a *floor area* where the public may congregate in a Group A *occupancy*,
- (d) in not less than 10% of the *suites* of a *hotel* or motel,
- (e) in a washroom for *public use* described in Sentence 3.8.2.3.(2), (3), (4) or (6), and
- (f) in the living space in a *suite* of *residential occupancy* in a Group C *major occupancy* apartment *building*.

4. Article 3.2.4.22. of Division B of the Regulation is amended by adding the following Sentence:(13) *Smoke alarms* described in Sentence (1) shall have a visual signalling component conforming to the requirements in 18.5.3. (Light, Color and Pulse Characteristics) of NFPA 72, “National Fire Alarm and Signaling Code”.**5. Sentence 3.3.4.9.(1) of Division B of the Regulation is revoked and the following substituted:**(1) If wood wall studs or sheet steel wall studs enclose the main bathroom in a *dwelling unit*, reinforcement shall be installed to permit the future installation of the following:

- (a) for a water closet, a grab bar described in Clauses 3.8.3.8.(3)(a) and a grab bar described in Clause 3.8.3.8.(3)(c),
- (b) for a shower, a grab bar described in Clause 3.8.3.13.(2)(f), and
- (c) for a bathtub, a grab bar described in Clause 3.8.3.13.(4)(c).

6. Article 3.4.6.1. of Division B of the Regulation is revoked and the following substituted:**3.4.6.1. Surface Finish of Ramps and Stairs**

(1) The surfaces of ramps, landings and treads shall,

- (a) have a finish that is slip-resistant, and
- (b) if accessible to the public, have a colour contrast or a distinctive visual pattern to demarcate,

- (i) the leading edge of the tread,
- (ii) the leading edge of the landing, and
- (iii) the beginning and end of a ramp.

(2) A tactile attention indicator conforming to Article 3.8.3.18. shall be installed,

- (a) at the top of the stairs starting one tread depth back from the edge of the top stair, and
- (b) at the leading edge of landings where a doorway opens onto stairs.

(3) Treads and landings of exterior *exit* stairs shall be designed to be free of ice and snow accumulations if the stairs,

- (a) are more than 10 m high, or
- (b) serve a *hotel*.

7. (1) Sentence 3.7.4.2.(7) of Division B of the Regulation is amended by striking out “universal toilet room” in the portion before Clause (a) and substituting “universal washroom”.

(2) Sentences 3.7.4.2.(8), (9) and (10) of Division B of the Regulation are revoked and the following substituted:

(8) Where one water closet is required for males and one water closet is required for females, the following may be provided in lieu of the water closets otherwise required by this Subsection:

- (a) one universal washroom conforming to Sentence 3.8.3.12.(1), and
- (b) one washroom containing one water closet that is permitted to be used by both sexes provided the door to the room can be locked from the inside.

(9) Both sexes are permitted to be served by a single water closet if the *occupant load* is not more than 10 persons in an *assembly occupancy* referred to in Article 3.7.4.3. except for,

- (a) elementary and secondary schools,
- (b) child care facilities,
- (c) places of worship, and
- (d) undertaking premises.

(10) Any shelf or projection above a lavatory shall be located so that it will not be a hazard.

(11) Except for *dwelling units*, lavatories required by Sentence (5) shall be equipped with faucets that,

- (a) operate automatically, or
- (b) have lever type handles that do not close under spring action.

8. Sentence 3.7.4.3.(1) of Division B of the Regulation is amended by striking out “Sentence 3.7.4.2.(8)” and substituting “Sentence 3.7.4.2.(9)”.

9. Sentence 3.8.1.1.(1) of Division B of the Regulation is amended by striking out “and” at the end of Clause (b), by adding “and” at the end of Clause (c) and by adding the following Clause:

- (d) *camps for housing of workers*.

10. Article 3.8.1.2. of Division B of the Regulation is revoked and the following substituted:

3.8.1.2. Entrances

(1) Except as provided in Sentence 3.13.8.1.(2), the number of *barrier-free* entrances into a *building* shall conform to Table 3.8.1.2.

**Table 3.8.1.2.
Minimum Number of Pedestrian Entrances Required to be Barrier-Free**

Forming Part of Sentence 3.8.1.2.(1)

Item	Column 1 Number of Pedestrian Entrances into <i>Building</i>	Column 2 Minimum Number of Pedestrian Entrances Required to Be <i>Barrier- Free</i>
1.	1 to 3	1
2.	4 or 5	2

Item	Column 1	Column 2
	Number of Pedestrian Entrances into <i>Building</i>	Minimum Number of Pedestrian Entrances Required to Be <i>Barrier-Free</i>
3.	More than 5	Not less than 50%

(2) One of the *barrier-free* entrances required by Sentence (1) shall be the principal entrance to the *building*.

(3) In addition to the *barrier-free* entrances required by Sentence (1), a *suite of assembly occupancy, business and personal services occupancy or mercantile occupancy* that is located in the *first storey* of a *building* or in a *storey* to which a *barrier-free* path of travel is provided, and that is separated from the remainder of the *building* so that there is no access to the remainder of the *building*, shall have at least one *barrier-free* entrance.

(4) A *barrier-free* entrance shall,

(a) be designed in accordance with Article 3.8.3.3., and

(b) lead from,

(i) the outdoors at sidewalk level, or

(ii) a ramp that conforms to Article 3.8.3.4. and leads from a sidewalk.

(5) At a *barrier-free* entrance that includes more than one doorway, only one of the doorways is required to be designed in accordance with Article 3.8.3.3.

(6) If a *walkway* or pedestrian bridge connects two *barrier-free storeys* in different *buildings*, the path of travel from one *storey* to the other *storey* by means of the *walkway* or bridge shall be *barrier-free*.

11. (1) Sentence 3.8.1.3.(4) of Division B of the Regulation is amended by striking out “1 600 mm in width and 1 600 in length” and substituting “1 800 mm in width and 1 800 mm in length”.

(2) Sentence 3.8.1.3.(5) of Division B of the Regulation is amended by striking out “from the floor” and substituting “from the finished floor”.

(3) Article 3.8.1.3. of Division B of the Regulation is amended by adding the following Sentence:

(6) A normally occupied *floor area* that is not required by Article 3.8.2.1. to have a *barrier-free* path of travel shall meet the following requirements:

(a) interior walking surfaces throughout the normally occupied *floor area* shall comply with Clauses (2)(a) to (e), and

(b) where the headroom of an area in a corridor or aisle in the normally occupied *floor area* is reduced to less than 1 980 mm, a guardrail or other barrier with its leading edge at or below 680 mm from the finished floor shall be provided.

12. Article 3.8.1.4. of Division B of the Regulation is revoked and the following substituted:

3.8.1.4. Escalators and Moving Walks

(1) In a *building* in which an escalator or inclined moving walk provides access to any floor level above or below the entrance floor level, an interior *barrier-free* path of travel shall be provided to that floor level.

(2) The route from the escalator or inclined moving walk to the *barrier-free* path of travel required by Sentence (1) shall be clearly indicated by appropriate signs.

(3) In a *building* in which a moving walk provides access between areas on the same floor level, a *barrier-free* path of travel shall be provided between the areas served by the moving walk.

13. Sentence 3.8.1.5.(1) of Division B of the Regulation is revoked and the following substituted:

(1) Except as required by Sentences 3.5.2.2.(1) and 3.8.3.5.(1) for elevators and Sentence 3.8.3.3.(17) for power door operator controls, controls for the operation of *building* services or safety devices, including electrical switches, thermostats and intercom switches, intended to be operated by the occupant and located in a *barrier-free* path of travel shall,

(a) be accessible to a person in a wheelchair using a side approach,

(b) be operable using a closed fist and with a force of not more than 22.2 N, and

(c) be mounted,

(i) 1 200 mm above the finished floor, in the case of a thermostat or a manual pull station, and

(ii) not less than 900 mm and not more than 1 100 mm above the finished floor, in the case of all other controls.

14. Article 3.8.2.1. of Division B of the Regulation is revoked and the following substituted:

3.8.2.1. Areas Requiring Barrier-Free Path of Travel

(1) Except as permitted by Sentence (3), a *barrier-free* path of travel from the entrances required by Sentences 3.8.1.2.(1) and (3) to be *barrier-free* shall be provided,

- (a) throughout the entrance *storey*,
- (b) except as permitted by Sentence (2), to and throughout all normally occupied *floor areas* and rooftop amenity spaces, and
- (c) throughout all normally occupied *floor areas* and rooftop amenity spaces that,
 - (i) are exempt from the application of Clause (b), and
 - (ii) are served by a passenger elevator, escalator, inclined moving walk, or other platform equipped passenger elevating device.

(2) A *barrier-free* path of travel described in Clause (1)(b) is not required to extend,

- (a) to *floor areas* or portions of *floor areas* containing a Group B, Division 2 or 3 *occupancy* that are not required by Article 3.5.2.1. to be connected by a ramp or served by an elevator,
- (b) to Group C or Group D *occupancies* that are in *floor areas* in a *building* that,
 - (i) is three or fewer *storeys* in *building height*, and
 - (ii) has a *building area* not exceeding 600 m²,
- (c) to Group F, Division 2 or 3 *occupancies* that are not required by Sentence 3.8.2.2.(1) to be served by an elevator,
- (d) to portions of restaurants and licensed beverage establishments where the same amenities and uses are provided on other *floor areas* that have a *barrier-free* path of travel, or
- (e) to portions of child care facilities that have all entrance doors at floor levels that do not have a *barrier-free* path of travel.

(3) A *barrier-free* path of travel described in Sentence (1) is not required to extend,

- (a) into *service rooms*,
- (b) into elevator machine rooms,
- (c) into janitors' rooms,
- (d) into *service spaces*,
- (e) into crawl spaces,
- (f) into *attic or roof spaces*,
- (g) into *high hazard industrial occupancies*,
- (h) to portions of a *floor area* with fixed seats in an *assembly occupancy* where these portions are not part of the *barrier-free* path of travel to,
 - (i) spaces designated for wheelchair use,
 - (ii) seats designated for *adaptable seating*, or
 - (iii) spaces for the storage of wheelchairs and *mobility assistive devices*,
- (i) to *suites of residential occupancy* that are in *storeys* other than the entrance *storey* and that have all entrance doors at floor levels that are not required to have a *barrier-free* path of travel,
- (j) except as required by Sentence (5), on the inside of a *suite of residential occupancy*, or
- (k) to portions of a *floor area* that are not at the same level as the entry level, provided amenities and uses provided on any raised or sunken level are accessible on the entry level by means of a *barrier-free* path of travel.

(4) In an *assembly occupancy* with fixed seats, the minimum number of spaces designated for wheelchair use and the minimum number of fixed seats designated for *adaptable seating* shall conform to Table 3.8.2.1.

**Table 3.8.2.1.
Designated Wheelchair Spaces and Adaptable Seating**

Forming Part of Sentence 3.8.2.1.(4)

Item	Column 1 Number of Fixed Seats in Seating Area	Column 2 Minimum Number of Spaces Designated for Wheelchairs	Column 3 Minimum Number of Fixed Seats Designated for <i>Adaptable Seating</i>
1.	Up to 20	2	1
2.	21 to 40	2	2
3.	41 to 60	2	3
4.	61 to 80	2	4
5.	81 to 100	3	5
6.	Over 100	3% of the seating capacity	The greater of 5 seats or 5% of the aisle seating capacity

(5) In a Group C *major occupancy* apartment building, not less than 15% of all *suites* of *residential occupancy* shall be provided with a *barrier-free* path of travel from the *suite* entrance door into the following rooms and spaces that shall be located at the same level as the *barrier-free* path of travel:

- (a) at least one bedroom,
- (b) at least one bathroom conforming to Sentence (6),
- (c) a kitchen or kitchen space, and
- (d) a living room or space.

(6) Bathrooms required by Clause (5)(b) shall,

- (a) contain a lavatory,
- (b) contain a water closet,
- (c) contain a bathtub or a shower,
- (d) have wall reinforcement installed in conformance with Sentence 3.3.4.9.(1), and
- (e) be designed to permit a wheelchair to turn in an open space not less than 1 500 mm in diameter.

(7) The number of *suites* described in Sentence (5) having 1, 2 or 3 or more bedrooms shall be in proportion to the number of *suites* of *residential occupancy* having 1, 2 or 3 or more bedrooms in the remainder of the *building*.

(8) The *suites* described in Sentence (5) shall be distributed among *storeys* that are required by Article 3.8.2.1. to have a *barrier-free* path of travel, having regard to the height of the *suite* above *grade*.

15. (1) Clause 3.8.2.2.(3)(a) of Division B of the Regulation is amended by striking out “1 500 mm wide and 6 m long” and substituting “2 440 mm wide and 7 400 mm long”.

(2) Clause 3.8.2.2.(3)(c) of Division B of the Regulation is amended by striking out “2 750 mm” and substituting “3 600 mm”.

16. Article 3.8.2.3. of Division B of the Regulation is revoked and the following substituted:

3.8.2.3. Washrooms Required to be Barrier-Free

(1) A *barrier-free* path of travel shall be provided to *barrier-free* washrooms designed to accommodate persons with disabilities in conformance with the requirements in Articles 3.8.3.8. to 3.8.3.12.

(2) The number of universal washrooms conforming to Article 3.8.3.12. provided in a *building* in which a washroom is required by Subsection 3.7.4. shall conform to Table 3.8.2.3.A.

Table 3.8.2.3.A.
Minimum Number of Universal Washrooms per Building

Forming Part of Sentence 3.8.2.3.(2)

Item	Column 1 Number of <i>Storeys</i> in <i>Building</i>	Column 2 Minimum Number of Universal Washrooms per <i>Building</i>
1.	1 to 3	1
2.	4 to 6	2
3.	Over 6	3, plus 1 for each additional increment of 3 <i>storeys</i> in excess of 6 <i>storeys</i>

(3) Where a washroom required by Subsection 3.7.4. is provided in a *storey* that is required by Article 3.8.2.1. to have a *barrier-free* path of travel,

- (a) the washroom shall conform to Articles 3.8.3.8. to 3.8.3.11., and
- (b) the number of *barrier-free* water closet stalls provided in the washroom shall conform to Table 3.8.2.3.B.

Table 3.8.2.3.B.
Minimum Number of Water Closet Stalls Required to be Barrier-Free

Forming Part of Sentence 3.8.2.3.(3)

Item	Column 1 Number of Water Closets per Washroom	Column 2 Minimum Number of <i>Barrier-Free</i> Water Closet Stalls per Washroom
1.	1 to 3	0, where a universal washroom is provided on the same floor level within 45 m of the washroom, or 1, where a universal washroom is not provided on the same floor level within 45 m of the washroom
2.	4 to 9	1
3.	10 to 16	2
4.	17 to 20	3
5.	21 to 30	4
6.	Over 30	5, plus 1 for each additional increment of 10 water closets per washroom in excess of 30 water closets per washroom

(4) Except as permitted in Sentence (5), where washrooms in excess of those required by Subsection 3.7.4. are provided in a *storey* that is required by Article 3.8.2.1. to have a *barrier-free* path of travel, the additional washrooms shall be designed to accommodate persons with disabilities in conformance with the requirements of,

- (a) Articles 3.8.3.8. to 3.8.3.11., or
- (b) Article 3.8.3.12.

(5) Washrooms need not conform to Sentence (4) provided,

- (a) they are located within *suites* of *residential occupancy*,
- (b) other *barrier-free* washrooms are provided on the same floor level within 45 m, or
- (c) they are located in an individual *suite* that is,
 - (i) used for a *business and personal services occupancy*, a *mercantile occupancy* or an *industrial occupancy*,
 - (ii) less than 300 m² in area, and
 - (iii) completely separated from, and without access to, the remainder of the *building*.

(6) Where a washroom required by Subsection 3.7.4. is provided in a *storey* that is not required by Article 3.8.2.1. to have a *barrier-free* path of travel, the washroom shall,

- (a) conform to Article 3.8.3.9. and Sentences 3.8.3.10.(5) and 3.8.3.11.(5), and
- (b) be provided with at least one ambulatory water closet stall conforming to Sentence 3.8.3.8.(10).

17. Article 3.8.2.4. of Division B of the Regulation is revoked and the following substituted:

3.8.2.4. Hotels

(1) Except as permitted in Sentence (2), at least 10% of the *suites* of a *hotel* shall,

- (a) have a *barrier-free* path of travel extending to,
 - (i) the inside of each room, and
 - (ii) a balcony where required by Sentence 3.3.1.7.(2), and
- (b) be distributed among *storeys* that are required by Article 3.8.2.1. to have a *barrier-free* path of travel, having regard to the height of the *suite* above *grade*.

(2) Not more than 20 *suites* need comply with Sentence (1).

(3) A *suite* having a *barrier-free* path of travel required by Sentence (1) shall have a bathroom that,

- (a) conforms to Clauses 3.8.3.12.(1)(a) to (h) and (j),
- (b) has an unobstructed area at least 1 200 mm in diameter extending the full height of the room, except that a door is permitted to open on the inside if it does not reduce the unobstructed area, and
- (c) has a bathtub or shower that conforms to Article 3.8.3.13.

(4) Except as required by Sentence 3.8.3.3.(17) for power door operator controls, controls for the operation of *building* services or safety devices, including electrical switches, thermostats and intercom switches, intended to be operated by the occupant and located within a *suite* having a *barrier-free* path of travel required by Sentence (1) shall conform to Sentence 3.8.1.5.(1).

(5) An entrance door to a *suite* having a *barrier-free* path of travel required by Sentence (1) shall have,

- (a) a power door operator conforming to Article 3.8.3.3., and
- (b) a door viewer located at a height no higher than 1 100 mm above the finished floor.

(6) Where a door is provided between a *suite* having a *barrier-free* path of travel required by Sentence (1) and an adjoining *suite*, the door shall conform to Sentences 3.8.3.3. (1) and (3).

(7) Where an emergency power supply is supplied by a generator, it shall supply at least one emergency power receptacle in at least one of the *suites* having a *barrier-free* path of travel required by Sentence (1).

(8) The emergency power receptacle described in Sentence (7) shall be identified with a legible sign having the words **EMERGENCY POWER OUTLET** permanently mounted on the wall beside the receptacle.

18. Article 3.8.3.1. of Division B of the Regulation is revoked and the following substituted:

3.8.3.1. Accessibility Signs

(1) Where a *building* is required to have a *barrier-free* entrance, signs incorporating the International Symbol of Access shall be installed to indicate the location of,

- (a) that entrance,
- (b) ramps located in a required *barrier-free* path of travel serving that entrance, and
- (c) an exterior passenger loading zone conforming to Sentence 3.8.2.2.(3), if one is provided.

(2) Where a washroom, elevator, telephone or parking area is required to accommodate persons with disabilities, it shall be identified by a sign consisting of the International Symbol of Access and such other graphic, tactile or written directions as are needed to indicate clearly the type of facility available.

(3) Where a washroom is not designed to accommodate persons with disabilities in a *storey* that is required by Article 3.8.2.1. to have a *barrier-free* path of travel, signs shall be provided to indicate the location of a washroom required to be *barrier-free*.

(4) Signs incorporating the International Symbol of Access shall be installed where necessary to indicate the location of a *barrier-free means of egress*.

(5) Where a wall mounted tactile sign is provided in a *building*, characters, symbols or pictographs on the sign shall be located not less than 1 200 mm and not more than 1 500 mm above the finished floor.

(6) Where a wall mounted tactile sign is provided in a *storey* that is not required by Article 3.8.2.1. to have a *barrier-free* path of travel, characters, symbols or pictographs on the sign shall conform to Sentence (5).

19. (1) Sentence 3.8.3.2.(1) of Division B of the Regulation is amended by striking out “and” at the end of Clause (f), by adding “and” at the end of Clause (g) and by adding the following Clause:

- (h) have a tactile attention indicator conforming to Article 3.8.3.18. that is located to identify an entry into a vehicular route or area where no curbs or any other element separate the vehicular route or area from a pedestrian route.

(2) Clause 3.8.3.2.(3)(b) of Division B of the Regulation is amended by striking out “1 200 mm” and substituting “1 500 mm”.

20. (1) Sentence 3.8.3.3.(1) of Division B of the Regulation is amended by striking out “850 mm” and substituting “860 mm”.

(2) Sentences 3.8.3.3.(3), (4), (5) and (6) of Division B of the Regulation are revoked and the following substituted:

(3) Door opening devices that are the only means of operation shall,

- (a) be designed to be operable using a closed fist, and
- (b) be mounted not less than 900 mm and not more than 1 100 mm above the finished floor.

(4) Except as permitted by Sentence (12), every door that provides a *barrier-free* path of travel through a *barrier-free* entrance required by Article 3.8.1.2. shall be equipped with a power door operator if the entrance serves a *building* containing a Group A, Group B, Division 2 or 3, Group C, Group D or Group E *occupancy*.

(5) Except as permitted by Sentence (12), where a *barrier-free* entrance required by Article 3.8.1.2. incorporates a vestibule, a door leading from the vestibule into the *floor area* shall be equipped with a power door operator in a *building* containing a Group A, Group B, Division 2 or 3, Group C, Group D or Group E *occupancy*.

(6) A door shall be equipped with a power door operator where the door serves,

- (a) a washroom for *public use* required to be *barrier-free*, or
- (b) a Group A *occupancy* within a Group C *major occupancy* apartment *building*.

(3) Sentence 3.8.3.3.(10) of Division B of the Regulation is amended by striking out “and” at the end of Clause (a), by adding “and” at the end of Clause (b) and by adding the following Clause:

- (c) 300 mm beyond both sides of a sliding door.

(4) Sentence 3.8.3.3.(11) of Division B of the Regulation is revoked and the following substituted:

(11) Vestibules located in a *barrier-free* path of travel,

- (a) shall be arranged to allow the movement of wheelchairs between doors, and
- (b) shall provide,
 - (i) where the doors into the vestibule are in series, a distance between the doors of at least 1 500 mm plus the width of any door that swings into the space in the path of travel from one door to another, and
 - (ii) where the doors into the vestibule are not aligned, a turning diameter of 1 500 mm within the vestibule clear of any door swing.

(5) Sentences 3.8.3.3.(16) and (17) of Division B of the Regulation are revoked and the following substituted:

(16) Where a power door operator is provided, it shall be installed on the latch side so as to allow persons to activate the opening of the door from either side.

(17) Except where a proximity scanning device is installed in conformance with Sentence (18), the control for a power door operator required by Sentence (4), (5) or (6) shall,

- (a) have a face dimension of not less than,
 - (i) 150 mm in diameter where the control is circular, or
 - (ii) 50 mm by 100 mm where the control is rectangular,
- (b) be operable using a closed fist,
- (c) be located so that,
 - (i) its centre is located not less than 900 mm and not more than 1 100 mm from the finished floor or ground, or
 - (ii) it extends from not more than 200 mm to not less than 900 mm above the finished floor or ground,

- (d) be located not less than 600 mm and not more than 1 500 mm beyond the door swing where the door opens towards the control,
- (e) be located in a clearly visible position, and
- (f) contain a sign incorporating the International Symbol of Access.

(18) A proximity scanning device that activates a power door shall be capable of detecting a person in a wheelchair.

(19) A normally occupied *floor area* that is not required by Article 3.8.2.1. to have a *barrier-free* path of travel shall comply with the following requirements:

- (a) all doorways in *public corridors* in the normally occupied *floor area* shall comply with Sentence (1),
- (b) door opening devices that are the only means of operation on doors in the normally occupied *floor area* shall comply with Sentence (3),
- (c) where a vision panel is provided in a door in the normally occupied *floor area*, the panel shall comply with Sentence (14),
- (d) doors consisting of a sheet of glass in the normally occupied *floor area* shall comply with Sentence (15), and
- (e) where a power door operator is installed for doors in the normally occupied *floor area*, it shall comply with Sentences (16) and (17).

21. (1) Subclause 3.8.3.4.(1)(d)(ii) of Division B of the Regulation is revoked and the following substituted:

- (ii) where there is a change of 90° or more in the direction of the ramp,

(2) Subclause 3.8.3.4.(1)(e)(v) of Division B of the Regulation is revoked and the following substituted:

- (v) be provided with a clearance of not less than 50 mm between the handrail and any wall or *guard* to which it is attached, and

(3) Sentence 3.8.3.4.(1) of Division B of the Regulation is amended by striking out “and” at the end of Subclause (f) (ii), by adding “and” at the end of Subclause (g)(ii) and by adding the following Clause:

- (h) except as provided in Sentence (2), where the ramp is wider than 2 200 mm, have an intermediate handrail with a clear width of 900 mm between the intermediate handrail and one of the handrails described in Clause (e).

(4) Sentence 3.8.3.4.(2) of Division B of the Regulation is revoked and the following substituted:

(2) Where a ramp serves as an aisleway for fixed seating, the requirements for handrails in Clauses (1)(e) and (h) and for walls or *guards* in Clause (1)(f) need not apply.

22. Article 3.8.3.6. of Division B of the Regulation is revoked and the following substituted:

3.8.3.6. Wheelchair Spaces and Adaptable Seating

(1) Spaces designated for wheelchair use required by Sentence 3.8.2.1.(4) shall be,

- (a) clear and level or level with removable seats,
- (b) not less than 900 mm wide and not less than,
 - (i) 1 525 mm long where designed to permit a wheelchair to enter from a side approach, and
 - (ii) 1 220 mm long where designed to permit a wheelchair to enter from the front or rear of the space,
- (c) arranged so that,
 - (i) at least two of the designated spaces are side by side, and
 - (ii) at least one fixed seat for a companion is located beside,
 - (A) each group of designated spaces, if two or more designated spaces are arranged side by side in a group, and
 - (B) each designated space that is not part of a group described in Sub-subclause (A),

(d) located adjoining a *barrier-free* path of travel without infringing on egress from any row of seating or any aisle requirements, and

(e) situated, as part of the designated seating plan, to provide a choice of viewing location and a clear view of the event taking place.

(2) Fixed seats designated for *adaptable seating* required by Sentence 3.8.2.1.(4) shall be,

- (a) located adjoining a *barrier-free* path of travel without infringing on egress from any row of seating or any aisle requirements,

- (b) equipped with a movable or removable armrest on the side of the seat adjoining the *barrier-free* path of travel, and
- (c) situated, as part of the designated seating plan, to provide a choice of viewing location and a clear view of the event taking place.

(3) In an *assembly occupancy* with fixed seats, space shall be provided for the storage of wheelchairs and *mobility assistive devices* in accordance with the following requirements:

- (a) at least one storage space not less than 810 mm by 1 370 mm shall be provided where the *assembly occupancy* has not more than 200 fixed seats and at least two such storage spaces shall be provided where the *assembly occupancy* has more than 200 fixed seats, and
- (b) the storage space or spaces shall be located on the same level and in proximity to the spaces designated for wheelchair use and seats designated for *adaptable seating*.

23. Articles 3.8.3.8. to 3.8.3.13. of Division B of the Regulation are revoked and the following substituted:

3.8.3.8. Water Closet Stalls

(1) Every *barrier-free* water closet stall in a washroom described in Sentence 3.8.2.3.(3) or (4) shall,

- (a) have a clear turning space at least 1 500 mm in diameter,
- (b) be equipped with a door that shall,
 - (i) be capable of being latched from the inside with a mechanism that is operable using a closed fist,
 - (ii) when the door is in an open position, have a clear opening of at least 860 mm,
 - (iii) swing outward, unless 820 mm by 1 440 mm clear floor area is provided within the stall to permit the door to be closed without interfering with the wheelchair,
 - (iv) be provided with spring-type or gravity hinges so that the door closes automatically,
 - (v) be provided with a door pull on both sides of the door, near the latch side of the door, located at a height not less than 900 mm and not more than 1 100 mm above the finished floor,
 - (vi) be aligned with a clear transfer space required by Subclause (2)(a)(ii) or Clause (2)(b), and
 - (vii) be capable of having the latch required by Subclause (i) released from the outside in case of an emergency,
- (c) be equipped with a water closet conforming to Article 3.8.3.9. that is located in accordance with Clause (2)(a) or (b),
- (d) Reserved
- (e) be equipped with a coat hook mounted not more than 1 200 mm above the finished floor on a side wall and projecting not more than 50 mm from the wall,
- (f) have a clearance of at least 1 700 mm between the outside of the stall face and the face of an in-swinging washroom door and 1 400 mm between the outside of the stall face and any wall-mounted fixture or other obstruction, and
- (g) where a toilet paper dispenser is provided, provide a dispenser that is,
 - (i) wall mounted,
 - (ii) located below the grab bar,
 - (iii) in line with or not more than 300 mm in front of the seat, and
 - (iv) not less than 600 mm above the finished floor.

(2) A water closet described in Clause (1)(c) shall be,

- (a) located so that,
 - (i) the centre line of the water closet is not less than 460 mm and not more than 480 mm from one side wall, and
 - (ii) a clear transfer space at least 900 mm wide and 1 500 mm deep is provided on the other side of the water closet, or
- (b) located so that a clear transfer space at least 900 mm wide and 1 500 mm deep is provided on each side of the water closet.
- (3) Where a water closet is located in accordance with Clause (2)(a),
 - (a) a grab bar conforming to Sentences (5) and (7) shall be provided on the side wall referred to in Subclause (2)(a)(i),
 - (b) a fold-down grab bar may be provided and, if one is provided, it shall conform to Sentence (8) and be provided on the side of the water closet opposite the grab bar described in Clause (a), and

- (c) a grab bar conforming to Sentences (6) and (7) shall be provided on the wall behind the water closet.
- (4)** Where a water closet is located in accordance with Clause (2)(b),
 - (a) a fold-down grab bar conforming to Sentence (8) shall be provided on each side of the water closet, and
 - (b) a grab bar conforming to Sentences (6) and (7) shall be provided on the wall behind the water closet.
- (5)** A grab bar described in Clause (3)(a) shall,
 - (a) be continuous L-shaped with 760 mm long horizontal and vertical components, and
 - (b) be wall mounted with the horizontal component 750 mm above the finished floor and the vertical component 150 mm in front of the water closet.
- (6)** A grab bar described in Clause (3)(c) or (4)(b) shall,
 - (a) be at least 600 mm in length, and
 - (b) be wall mounted horizontally from 840 mm to 920 mm above the finished floor and, where the water closet has a water tank, be wall mounted 150 mm above the tank.
- (7)** A grab bar described in Clause (3)(a) or (c) or (4)(b) shall,
 - (a) be installed to resist a load of at least 1.3 kN applied vertically or horizontally,
 - (b) be not less than 35 mm and not more than 40 mm in diameter,
 - (c) have a clearance of 50 mm from the wall, and
 - (d) have a slip-resistant surface.
- (8)** A fold-down grab bar described in Clause (3)(b) or (4)(a) shall,
 - (a) be mounted on the wall behind the water closet,
 - (i) with the horizontal component 750 mm above the finished floor, and
 - (ii) not less than 390 mm and not more than 410 mm from the centre line of the water closet,
 - (b) not require a force of more than 22.2 N to pull it down,
 - (c) be at least 760 mm in length,
 - (d) be installed to resist a load of at least 1.3 kN applied vertically or horizontally,
 - (e) be not less than 35 mm and not more than 40 mm in diameter, and
 - (f) have a slip-resistant surface.
- (9)** A fold-down grab bar installed in accordance with Sentence (8) is permitted to encroach into,
 - (a) the clear turning space described in Clause (1)(a), or
 - (b) a clear transfer space described in Subclause (2)(a)(ii) or Clause (2)(b).
- (10)** Where an ambulatory water closet stall is required by Sentence 3.8.2.3.(6), it shall,
 - (a) be at least 1 500 mm in depth and be not less than 890 mm and not more than 940 mm in width,
 - (b) be equipped with a door that shall,
 - (i) be capable of being latched from the inside with a mechanism that is operable using a closed fist,
 - (ii) when the door is in an open position, have a clear opening of at least 810 mm,
 - (iii) swing outward, unless the minimum dimensions in Clause (a) are not located within the door swing,
 - (iv) be provided with spring-type or gravity hinges so that the door closes automatically,
 - (v) be provided with a door pull on both sides of the door, near the latch side of the door, located at a height not less than 900 mm and not more than 1 000 mm above the finished floor, and
 - (vi) be capable of having the latch required by Subclause (i) released from the outside in the case of an emergency,
 - (c) be equipped with a water closet conforming to Article 3.8.3.9. and located so that its centre line is centred between the partition walls,
 - (d) be equipped on each side of the water closet with grab bars conforming to Clause (3)(a), and
 - (e) be equipped with a coat hook conforming to Clause (1)(e).

3.8.3.9. Water Closets

- (1) A water closet described in Clause 3.8.3.8.(1)(c) or (10)(c) or 3.8.3.12.(1)(d) shall,
- (a) be equipped with a seat located at not less than 430 mm and not more than 485 mm above the finished floor,
 - (b) be equipped with hand-operated flushing controls that are easily accessible to a wheelchair user or be automatically operable,
 - (c) be equipped with a back support where there is no seat lid or tank, and
 - (d) not have a spring-activated seat.
- (2) Hand-operated flushing controls required by Clause (1)(b) shall be operable using a closed fist and with a force of not more than 22.2 N.

3.8.3.10. Urinals

- (1) Where more than one urinal is provided in a washroom described in Sentence 3.8.2.3.(3) or (4), at least one urinal shall be,
- (a) wall mounted, with the rim located not more than 430 mm above the finished floor, or
 - (b) floor mounted, with the rim level with the finished floor.
- (2) A urinal described in Sentence (1) shall have,
- (a) no step in front,
 - (b) a vertically mounted grab bar installed on each side of the urinal that,
 - (i) is not less than 300 mm long,
 - (ii) has its centre line 1 000 mm above the finished floor,
 - (iii) is located not less than 380 mm and not more than 450 mm measured horizontally from the vertical centre line of the urinal, and
 - (iv) complies with Sentence 3.8.3.8.(7), and
 - (c) a minimum depth of 345 mm measured from the outer face of the urinal rim to the back of the fixture.
- (3) Where manual flush controls are provided for a urinal described in Sentence (1), the flush controls shall be,
- (a) operable using a closed fist, and
 - (b) mounted no higher than 1 200 mm above the finished floor.
- (4) Where privacy screens are installed for a urinal described in Sentence (1), they shall,
- (a) be mounted a minimum of 460 mm from the centre line of the urinal, and
 - (b) have a clearance of at least 50 mm from the grab bars required by Clause (2)(b).
- (5) Where more than one urinal is provided in a washroom described in Sentence 3.8.2.3.(6), at least one urinal conforming to Sentences (1) to (4) shall be provided in the washroom.

3.8.3.11. Lavatories

- (1) A washroom described in Sentence 3.8.2.3.(2), (3) or (4) shall be provided with a lavatory that shall,
- (a) be located so that the distance between the centre line of the lavatory and the side wall is not less than 460 mm,
 - (b) be mounted so that the top of the lavatory is not more than 840 mm above the finished floor,
 - (c) have a clearance beneath the lavatory not less than,
 - (i) 920 mm wide,
 - (ii) 735 mm high at the front edge,
 - (iii) 685 mm high at a point 205 mm back from the front edge, and
 - (iv) 350 mm high from a point 300 mm back from the front edge to the wall,
 - (d) have insulated pipes where they would otherwise present a burn hazard or have water supply temperature limited to a maximum of 43°C,
 - (e) be equipped with faucets that have lever type handles without spring loading or operate automatically and that are located so that the distance from the centre line of the faucet to the edge of the basin or, where the basin is mounted in a vanity, to the front edge of the vanity, is not more than 485 mm,

- (f) have a minimum 1 370 mm deep floor space to allow for a forward approach, of which a maximum of 500 mm can be located under the lavatory,
- (g) have a soap dispenser that is,
 - (i) located to be accessible to persons in wheelchairs,
 - (ii) located so that the dispensing height is not more than 1 200 mm above the finished floor,
 - (iii) located not more than 610 mm, measured horizontally, from the edge of the lavatory, and
 - (iv) operable with one hand, and
- (h) have a towel dispenser or other hand drying equipment that is,
 - (i) located to be accessible to persons in wheelchairs,
 - (ii) located so that the dispensing height is not more than 1 200 mm above the finished floor,
 - (iii) operable with one hand, and
 - (iv) located not more than 610 mm, measured horizontally, from the edge of the lavatory.
- (2) If mirrors are installed in a washroom described in Sentence 3.8.2.3.(2), (3) or (4), at least one mirror shall be,
 - (a) installed above a lavatory required by Sentence (1), and
 - (b) mounted with its bottom edge not more than 1 000 mm above the finished floor or inclined to the vertical to be usable by a person in a wheelchair.
- (3) If dispensing or hand-operated washroom accessories, except those located in water closet stalls or described in Clause (1)(g), are provided, they shall be mounted so that,
 - (a) the dispensing height is not less than 900 mm and not more than 1 200 mm above the finished floor,
 - (b) the controls or operating mechanisms are mounted not less than 900 mm and not more than 1 200 mm above the finished floor, and
 - (c) a minimum 1 370 mm deep floor space is provided in front of the controls or operating mechanisms to allow for a front approach.
- (4) Where a shelf is installed above a lavatory required by Sentence (1), it shall,
 - (a) be located not more than 200 mm above the top of the lavatory and not more than 1 100 mm above the finished floor, and
 - (b) project not more than 100 mm from the wall.
- (5) A washroom described in Sentence 3.8.2.3.(6) shall be provided with a lavatory conforming to Clauses (1)(e), (g) and (h).

3.8.3.12. Universal Washrooms

- (1) A universal washroom shall,
 - (a) be served by a *barrier-free* path of travel,
 - (b) have a door that is capable of being locked from the inside and released from the outside in case of emergency and that has,
 - (i) a graspable latch-operating mechanism located not less than 900 mm and not more than 1 000 mm above the finished floor,
 - (ii) if it is an outward swinging door, a door pull not less than 140 mm long located on the inside so that its midpoint is not less than 200 mm and not more than 300 mm from the latch side of the door and not less than 900 mm and not more than 1 000 mm above the finished floor, and
 - (iii) if it is an outward swinging door, a door closer, spring hinges or gravity hinges, so that the door closes automatically,
 - (c) have one lavatory conforming to Sentences 3.8.3.11.(1), (3) and (4),
 - (d) have one water closet conforming to Article 3.8.3.9. that is located in accordance with Clause 3.8.3.8.(2)(a) or (b),
 - (e) have grab bars conforming to,
 - (i) Sentence 3.8.3.8.(3), if the water closet is located in accordance with Clause 3.8.3.8.(2)(a), or
 - (ii) Sentence 3.8.3.8.(4), if the water closet is located in accordance with Clause 3.8.3.8.(2)(b),

- (f) have no internal dimension between walls that is less than 1 700 mm,
- (g) have a coat hook conforming to Clause 3.8.3.8.(1)(e) and a shelf located not more than 1 200 mm above the finished floor,
- (h) be designed to permit a wheelchair to turn in an open space not less than 1 700 mm in diameter,
- (i) be provided with a door equipped with a power door operator if the door is equipped with a self-closing device,
- (j) be provided with a mirror,
 - (i) installed above a lavatory described in Clause (1)(c), and
 - (ii) mounted with its bottom edge not more than 1 000 mm above the finished floor or inclined to the vertical to be usable by a person in a wheelchair, and
- (k) have lighting controlled by a motion sensor conforming to Sentence 12.2.4.1.(2).
- (2)** A universal washroom shall have,
 - (a) an emergency call system that consists of audible and visual signal devices inside and outside of the washroom that are activated by a control device inside the washroom, and
 - (b) an emergency sign that contains the words **IN THE EVENT OF AN EMERGENCY PUSH EMERGENCY BUTTON AND AUDIBLE AND VISUAL SIGNAL WILL ACTIVATE** in letters at least 25 mm high with a 5 mm stroke and that is posted above the emergency button.
- (3)** A clear space not less than 810 mm wide and 1 830 mm long shall be provided in each universal washroom for an adult-size change table.
- (4)** Where the clear space provided for an adult-size change table is adjacent to a wall, reinforcement shall be installed in the wall to permit the future installation of the change table.
- (5)** Where an adult-size change table is installed, it shall,
 - (a) when fully loaded, have a surface height above the finished floor that can be adjusted from between 450 mm and 500 mm at the low range to between 850 mm and 900 mm at the high range,
 - (b) be designed to carry a minimum load of 1.33 kN,
 - (c) have a clear floor space parallel to the long side of the table not less than 760 mm wide and 1 500 mm long, and
 - (d) in the case of a fold-down table,
 - (i) be installed so that it does not encroach into a clear transfer space described in Clause 3.8.3.8.(2)(a) or (b), and
 - (ii) have no operating mechanisms higher than 1 200 mm.
- (6)** A universal washroom need not conform to Sentences (3) and (4) if,
 - (a) it is located in an individual *suite* that,
 - (i) is used for an *assembly occupancy*, a *business and personal services occupancy*, a *mercantile occupancy* or an *industrial occupancy*, and
 - (ii) is less than 300 m² in *building area*, or
 - (b) another universal washroom conforming to this Article is provided on the same floor level within 45 m.

3.8.3.13. Showers and Bathtubs

(1) Except within a *suite* of *residential occupancy*, if showers are provided in a *building*, the number of *barrier-free* showers shall conform to Table 3.8.3.13.

Table 3.8.3.13.
Minimum Number of Barrier-Free Showers

Forming Part of Sentence 3.8.3.13.(1)

Item	Column 1 Number of Showers provided in a Group	Column 2 Minimum Number of Showers Required to Be <i>Barrier-Free</i>
1.	1	0
2.	2 to 7	1

Item	Column 1	Column 2
	Number of Showers provided in a Group	Minimum Number of Showers Required to Be <i>Barrier-Free</i>
3.	Over 7	1, plus 1 for each additional increment of 7 showers in a group

(2) A *barrier-free* shower required by Sentence (1) shall,

- (a) be not less than 1 500 mm wide and 900 mm deep,
- (b) have a clear floor space at the entrance to the shower not less than 900 mm deep and the same width as the shower, except that fixtures are permitted to project into that space provided they do not restrict access to the shower,
- (c) have a slip-resistant floor surface,
- (d) have a threshold that is level with the adjacent finished floor or a bevelled threshold not more than 13 mm higher than the adjacent finished floor,
- (e) have a hinged seat that is not spring-loaded or a fixed seat that shall be,
 - (i) not less than 450 mm wide and 400 mm deep,
 - (ii) mounted not less than 430 mm and not more than 485 mm above the finished floor,
 - (iii) designed to carry a minimum load of 1.3 kN, and
 - (iv) located so that the edge of the seat is within 500 mm of the shower controls,
- (f) have a wall mounted continuous L-shaped grab bar conforming to Sentence 3.8.3.8.(7) and located between the shower head and the controls, with the horizontal component of the grab bar mounted not more than 850 mm above the finished floor,
- (g) have a pressure-equalizing or thermostatic mixing valve controlled by a lever or other device operable using a closed fist from the seated position,
- (h) have a hand-held shower head with not less than 1 500 mm of flexible hose located so that it can be reached from the seated position and equipped with a support so that it can operate as a fixed shower head, and
- (i) have fully recessed soap holders that can be reached from the seated position.

(3) Individual showers that are provided for use by patients or residents in *buildings* of Group B, Division 2 or 3 *occupancy* shall conform to Sentence (2).

(4) Individual bathtubs that are provided for the use of patients or residents in *buildings* of Group B, Division 2 or 3 *occupancy* shall have,

- (a) faucets that have lever type handles without spring loading or that operate automatically,
- (b) faucet handles that are located so as to be usable by a person seated in the bathtub,
- (c) unless the bathtub is free-standing, a continuous L-shaped grab bar conforming to Sentence 3.8.3.8.(7) with 900 mm long horizontal and vertical components mounted with,
 - (i) the horizontal component located not less than 150 mm and not more than 200 mm above and parallel to the rim of the bathtub, and
 - (ii) the vertical component located not less than 300 mm and not more than 450 mm from the control end of the bathtub, and
- (d) unless the bathtub is free-standing, a grab bar conforming to Sentence 3.8.3.8.(7) that is located at each end of the bathtub and is,
 - (i) at least 760 mm long,
 - (ii) mounted vertically from a point 200 mm above the rim of the bathtub, and
 - (iii) mounted within 150 mm from the edge of the bathtub, measured horizontally.

(5) Where a *barrier-free* bathtub is provided, a clear floor space at least 900 mm wide and 1 440 mm long shall be provided along the full length of the bathtub.

24. Articles 3.8.3.15. and 3.8.3.16. of Division B of the Regulation are revoked and the following substituted:

3.8.3.15. Shelves or Counters for Telephones

(1) Where more than one telephone is provided for public use, a built-in shelf or counter shall be provided for at least one telephone.

(2) A shelf or counter described in Sentence (1) shall,

- (a) be level,
- (b) be not less than 500 mm wide and 350 mm deep, and
- (c) have, for each telephone provided, a clear space that,
 - (i) is not less than 810 mm wide and 1 370 mm deep, centred on the telephone, and
 - (ii) has no obstruction within 250 mm above the surface.

(3) The top surface of a section of the shelf or counter described in Sentence (1) shall,

- (a) be located not less than 775 mm and not more than 875 mm from the finished floor, and
- (b) have a knee space not less than 740 mm high.

(4) Where a wall-hung telephone is provided above the shelf or counter section described in Sentence (3), it shall be located so that the receiver and coin or card slot are not more than 1 200 mm from the finished floor.

(5) Where more than one telephone is provided for public use in a normally occupied *floor area* that is not required by Article 3.8.2.1. to have a *barrier-free* path of travel, a built-in shelf or counter that conforms to Sentences (2), (3) and (4) shall be provided for at least one telephone.

3.8.3.16. Drinking Fountains

(1) Where more than one drinking fountain is provided, at least one shall be a *barrier-free* fountain that conforms to Sentences (2) and (3).

(2) A *barrier-free* drinking fountain shall,

- (a) have a spout located near the front of the unit not more than 915 mm above the finished floor,
- (b) be equipped with controls that are easily operated from a wheelchair using one hand with a force of not more than 22 N or operates automatically,
- (c) project the water at least 100 mm high,
- (d) provide the water stream at a vertical angle of up to,
 - (i) 30°, where the spout is located less than 75 mm from the front of the fountain, or
 - (ii) 15°, where the spout is located not less than 75 mm and not more than 125 mm from the front of the fountain,
- (e) be detectable by a cane at a level at or below 680 mm from the finished floor, and
- (f) where the drinking fountain is cantilevered, meet the following requirements:
 - (i) be mounted not more than 915 mm above the finished floor,
 - (ii) provide a clearance height under the fountain of not less than 735 mm above the finished floor,
 - (iii) have a clear depth under the fountain of not less than 500 mm,
 - (iv) have a clear width under the fountain of not less than 760 mm,
 - (v) have a toe clearance height under the fountain of at least 350 mm above the finished floor from a point 300 mm back from the front edge to the wall, and
 - (vi) have a depth at the base of the fountain of at least 700 mm.

(3) A *barrier-free* drinking fountain required by Sentence (1) shall have a clear floor space in front of, or adjacent to, the fountain that is a minimum of 810 mm deep and 1 370 mm wide.

(4) Where more than one drinking fountain is provided in a normally occupied *floor area* that is not required by Article 3.8.2.1. to have a *barrier-free* path of travel, at least one shall be a *barrier-free* fountain that conforms to Sentences (2) and (3).

3.8.3.17. Platforms

(1) A tactile attention indicator conforming to Article 3.8.3.18. shall be installed along any edge of a platform that is,

- (a) not protected by a *guard*, and
- (b) higher than 250 mm above the finished floor or ground or sloped steeper than 1 in 3.

- (2) Sentence (1) does not apply to the front edges of *stages*.

3.8.3.18. Tactile Attention Indicators

(1) Where a tactile attention indicator is required, it shall conform to Clauses 4.1.1. and 4.1.2. of ISO 23599, “Assistive Products for Blind and Vision-Impaired Persons – Tactile Walking Surface Indicators”.

25. (1) Sentence 3.11.3.1.(1) of Division B of the Regulation is amended by striking out “Sentences (2) to (26)” at the end and substituting “Sentences (2) to (26) and Articles 3.11.3.2. and 3.11.3.3.”.

(2) Sentence 3.11.3.1.(3) of Division B of the Regulation is amended by striking out “persons who are disabled or ill” and substituting “persons with disabilities or persons who are ill”.

(3) Clause 3.11.3.1.(4)(e) of Division B of the Regulation is amended by striking out “Sentence 3.11.5.1.(1)” at the end and substituting “Sentence 3.11.5.2.(1)”.

(4) Sentence 3.11.3.1.(8) of Division B of the Regulation is amended by striking out “Sentence 3.11.5.1.(1)” and substituting “Sentence 3.11.5.2.(1)”.

(5) Clause 3.11.3.1.(9)(a) of Division B of the Regulation is revoked and the following substituted:

- (a) except for a pool described in Sentence 3.11.5.2.(1), be not less than 1 800 mm wide,

(6) Sentence 3.11.3.1.(14) of Division B of the Regulation is revoked and the following substituted:

(14) Except for a *modified pool* and *wave action pool*, the perimeter of the *pool deck* shall be clearly delineated by a tactile attention indicator conforming to Article 3.8.3.18. and located where any area contiguous to the *pool deck* may be confused with the deck.

(7) Sentence 3.11.3.1.(18) of Division B of the Regulation is revoked and the following substituted:

(18) Except for a *modified pool* and *wave action pool*, at least,

- (a) one ladder or set of steps shall be provided in both the deep and shallow areas of a *public pool* for entry into and egress from the pool water, and
- (b) one *barrier-free* access shall be provided for entry into and egress from the water of a *public pool* as required by Article 3.11.3.3.

(8) Sentence 3.11.3.1.(25) of Division B of the Regulation is revoked and the following substituted:

(25) Except for a *modified pool* and a pool to which Sentence 3.11.5.2.(2) applies, every *public pool* having a maximum water depth of 2 500 mm or less shall display a warning notice posted in a location clearly visible to divers on which are printed in letters at least 150 mm high the words **CAUTION — AVOID DEEP DIVES** or **SHALLOW WATER — NO DIVING**.

26. Subsection 3.11.3. of Division B of the Regulation is amended by adding the following Articles:

3.11.3.2. Barrier-Free Path of Travel for Outdoor Pool Deck

(1) Where an *outdoor pool* is provided, a *barrier-free* path of travel shall be provided to and throughout the normally occupied portions of the *pool deck*.

3.11.3.3. Access into Public Pools

(1) Access for entry into and egress from the water of a *public pool* provided in a *storey* that is required by Article 3.8.2.1. to have a *barrier-free* path of travel shall be *barrier-free* and shall be provided by,

- (a) a ramp conforming to,
 - (i) Article 3.11.5.1., and
 - (ii) Article 3.11.5.2., in the case of a pool described in Sentence 3.11.5.2.(1), or
- (b) a pool lift conforming to the manufacturer’s specifications and installation instructions and conforming to Sentences (2) to (6).

(2) Except where the entire pool depth is greater than 1 220 mm, where a pool lift is installed, at least one lift shall be located where the water level does not exceed 1 220 mm.

(3) The centre line of the seat for the pool lift shall be located over the deck and a minimum of 400 mm from the edge of the pool when in the raised position.

(4) A clear deck space located parallel with the seat for the pool lift and on the side of the seat opposite the water shall,

- (a) be at least 915 mm wide, and
- (b) extend forward not less than 1 220 mm from a line located 305 mm behind the rear edge of the seat.

- (5) The pool lift shall be,
 - (a) designed to be operable without assistance from both the deck and water, and
 - (b) designed so that, when in use, its controls and operating mechanisms are unobstructed.
- (6) The pool lift shall,
 - (a) have a weight capacity of at least 135 kg, and
 - (b) be capable of sustaining a static load of at least 1.5 times the rated load.

27. Subsection 3.11.5. of Division B of the Regulation is revoked and the following substituted:

3.11.5. Ramps into Public Pools

3.11.5.1. Ramps into Public Pools

(1) Where *barrier-free* access for entry into and egress from the water of a *public pool* is provided by a ramp as required by Clause 3.11.3.3.(1)(a), the pool shall be designed and constructed in accordance with Sentences (2) to (4).

- (2) A ramp shall have,
 - (a) along each side a handrail that,
 - (i) has a height of not less than 865 mm and not more than 965 mm, and
 - (ii) runs parallel to the slope of the ramp,
 - (b) a width of at least 1 100 mm,
 - (c) a curb or other means to prevent a wheelchair from falling off the side of the ramp,
 - (d) surface finishes capable of being kept clean, sanitary and free from slipperiness, and
 - (e) a landing at the bottom at least 1 500 mm in length and the same width as the ramp.

(3) Where a ramp that is not submerged is adjacent to the pool wall and is used for access to the water, the pool shall be constructed so that,

- (a) the landing at the bottom of the ramp is at least 450 mm but not more than 550 mm below the top of the wall separating the ramp from the pool,
- (b) the landing is equipped with a floor drain at its lowest point,
- (c) the top of the wall between the pool and the ramp is at least 250 mm and not more than 300 mm in width,
- (d) the *pool deck* is capable of accommodating a movable barrier separating the deck from the ramp,
- (e) the water depth at the landing is accurately and clearly marked at the landing in figures at least 100 mm high on the top of the wall separating the pool from the ramp, and
- (f) the ramp has a slope not exceeding 1 in 12.

(4) Where a submerged ramp is adjacent to the pool wall and is used for access to the water, the pool shall be constructed so that,

- (a) the water depth at the bottom of the ramp is at least 600 mm and not greater than 900 mm,
- (b) a hard-surfaced area that is at least 750 mm wide is contiguous to the entire length of the part of the submerged ramp that pierces any part of the deck,
- (c) the area described in Clause (b) is capable of accommodating a movable barrier separating the area from the deck,
- (d) the finishes in submerged portions of the ramps and curbs are different in colour or shade from each other and from that of the pool walls and bottom, and
- (e) the submerged ramp has a slope not exceeding 1 in 9.

3.11.5.2. Public Pools in Group B, Division 2 or 3 Major Occupancies

(1) Despite Sentences 3.11.3.1.(4) and (8) and Clause 3.11.3.1.(9)(a), where a *public pool* is constructed in a *building* containing a Group B, Division 2 or 3 *major occupancy* and has a water depth not exceeding 1 500 mm and a water surface area not exceeding 100 m², the *pool deck* contiguous to not more than 50% of the total perimeter of the pool may be replaced by one or more ramps that will permit a bather seated in a wheelchair to enter the water with or without the wheelchair.

(2) Despite Sentence 3.11.3.1.(25), a warning notice, on which are printed in letters at least 150 mm high the words **CAUTION — NO DIVING**, shall be posted conspicuously on each wall or fence line enclosing a pool described in Sentence (1).

(3) There shall be a curb along the perimeter of a pool described in Sentence (1) except at steps, ladders and ramp entrances.

(4) The curb required by Sentence (3) shall have,

- (a) a height of 50 mm,
- (b) rounded edges,
- (c) a coved base, and
- (d) a raised nosing at the top to serve as a fingerhold for a bather in the water.

28. (1) Sentence 3.11.6.1.(1) of Division B of the Regulation is revoked and the following substituted:

(1) A *modified pool* is exempt from Sentences 3.11.3.1.(4) to (9), (12), (13), (14), (16), (17), (18), (21), (23), (24) and (25), Sentence 3.11.8.1.(12) and Article 3.11.3.3.

(2) Sentence 3.11.6.1.(4) of Division B of the Regulation is amended by striking out “exceed 8%” at the end and substituting “exceed 1 in 12”.

29. (1) Sentence 3.11.7.1.(1) of Division B of the Regulation is revoked and the following substituted:

(1) A *wave action pool* is exempt from Sentences 3.11.3.1.(4) to (9), (12), (13), (14), (17), (18) and (23), Sentence 3.11.8.1.(12) and Article 3.11.3.3.

(2) Sentence 3.11.7.1.(3) of Division B of the Regulation is revoked and the following substituted:

(3) The slope of the bottom of any portion of a *wave action pool*,

- (a) shall not exceed 1 in 12 where the still water depth is less than 1 000 mm, and
- (b) shall not exceed 1 in 9 where the still water depth is 1 000 mm or more.

30. Subsection 3.12.3. of Division B of the Regulation is revoked and the following substituted:

3.12.3. Ramps and Access into Public Spas

3.12.3.1. Ramps into Public Spas

(1) Not more than 50% of the total perimeter of a *public spa* may be replaced by one or more ramps that permit a bather seated in a wheelchair to enter the water with or without the wheelchair.

(2) If a *public spa* has one or more ramps described in Sentence (1), the *public spa* shall comply with Article 3.11.5.1. and Sentences 3.11.5.2.(3) and (4).

3.12.3.2. Access into Public Spas

(1) Where more than one *public spa* is provided within a *suite* located on a *storey* that is required by Article 3.8.2.1. to have a *barrier-free* path of travel, a *barrier-free* access described in Sentence (2) shall be provided to at least one *public spa*.

(2) *Barrier-free* access for entry into and egress from a *public spa* shall be provided by,

- (a) a ramp conforming to Article 3.12.3.1.,
- (b) a pool lift conforming to the manufacturer’s specifications and installation instructions and conforming to Sentences 3.11.3.3.(2) to (6), or
- (c) a transfer wall conforming to Sentences (3) to (5).

(3) A transfer wall providing *barrier-free* access for entry into and egress from a *public spa* shall,

- (a) have a height not less than 405 mm and not more than 485 mm measured from the *pool deck*,
- (b) have a depth of at least 300 mm and not more than 400 mm,
- (c) be slip-resistant and have edges that are rounded, and
- (d) have at least one grab bar that,
 - (i) is perpendicular to the pool and extends the full depth of the transfer wall,
 - (ii) is located not less than 100 mm and not more than 150 mm above the transfer wall,
 - (iii) has a clearance of at least 610 mm on both sides,
 - (iv) complies with Clauses 3.8.3.8.(7)(a) and (b), and
 - (v) is made of a slip-resistant material.

(4) The deck area required to make a lateral transfer to the transfer wall shall,

- (a) be outside and adjacent to the *barrier-free* path of travel described in Sentence (1),
- (b) have no obstructions at the side of the transfer wall serving the transfer space,
- (c) have a clear space of 900 mm by 2 200 mm, and
- (d) have a slope less than 2% provided at the base of the transfer wall surface.

(5) The deck area described in Clause (4)(c) shall be centred on,

- (a) the grab bar where one grab bar is provided, or
- (b) the clear space between the grab bars where more than one grab bar is provided.

31. Article 3.13.8.1. of Division B of the Regulation is revoked and the following substituted:

3.13.8.1. Application

- (1) Except as provided in this Subsection, the requirements in Section 3.8. apply to *rapid transit stations*.
- (2) A *rapid transit station* need not be provided with more than one *barrier-free* entrance described in Article 3.8.1.2.
- (3) At least one *barrier-free* path of travel shall be provided from a *barrier-free* entrance,
 - (a) into the *fare-paid area*, and
 - (b) to each platform.

32. Sentence 3.13.8.3.(1) of Division B of the Regulation is revoked and the following substituted:

(1) Except as provided in Sentence (2), the elevator described in Article 3.13.8.2. shall be capable of providing transportation from each platform to a *barrier-free* entrance described in Article 3.8.1.2.

33. Sentence 9.5.2.3.(1) of Division B of the Regulation is revoked and the following substituted:

(1) If wood wall studs or sheet steel wall studs enclose the main bathroom in a *dwelling unit*, reinforcement shall be installed to permit the future installation of the following:

- (a) for a water closet, a grab bar described in Clauses 3.8.3.8.(3)(a) and a grab bar described in Clause 3.8.3.8.(3)(c),
- (b) for a shower, a grab bar described in Clause 3.8.3.13.(2)(f), and
- (c) for a bathtub, a grab bar described in Clause 3.8.3.13.(4)(c).

34. (1) Sentence 9.8.9.6.(1) of Division B of the Regulation is amended by striking out “Except as required in Sentence (4)” at the beginning in the portion before Clause (a) and substituting “Except as required by Sentence (5)”.

(2) Sentences 9.8.9.6.(3) and (4) of Division B of the Regulation are revoked and the following substituted:

(3) Stairs and ramps, except those serving a single *dwelling unit*, *service rooms* or *service spaces*, shall have a colour contrast or a distinctive visual pattern to demarcate,

- (a) the leading edge of the treads,
- (b) the leading edge of the landing, and
- (c) the beginning and end of a ramp.

(4) Except for stairs serving a single *dwelling unit*, *service rooms* or *service spaces*, a tactile attention indicator conforming to Article 3.8.3.18. shall be installed,

- (a) at the top of the stairs starting one tread depth back from the edge of the top stair, and
- (b) at the leading edge of landings where a doorway opens onto stairs.

(5) Treads and landings of interior and exterior stairs and ramps, other than those within *dwelling units*, shall have a slip-resistant finish or be provided with slip-resistant strips that extend not more than 1 mm above the surface.

35. Article 9.10.19.1. of Division B of the Regulation is amended by adding the following Sentence:

(2) *Smoke alarms* described in Sentence (1) shall have a visual signalling component conforming to the requirements in 18.5.3. (Light, Color and Pulse Characteristics) of NFPA 72, “National Fire Alarm and Signaling Code”.

36. Sentence 9.10.19.3.(3) of Division B of the Regulation is revoked and the following substituted:

(3) A *smoke alarm* required in Sentence (1) shall have a visual signalling component conforming to the requirements in 18.5.3. (Light, Color and Pulse Characteristics) of NFPA 72, “National Fire Alarm and Signaling Code”.

(4) *Smoke alarms* required in Article 9.10.19.1. and Sentence (1) shall be installed on or near the ceiling.

37. Article 11.3.3.2. of Division B of the Regulation is revoked and the following substituted:

11.3.3.2. Extensive Renovation

(1) Where existing interior walls or ceilings or floor assemblies or roof assemblies are substantially removed in an existing *building* and new interior walls, ceilings, floor assemblies or roof assemblies are installed in the *building*, structural and fire-resistance elements shall be constructed in compliance with the requirements of the other Parts.

(2) Except as provided in Section 11.5., the proposed *construction* within an existing *suite* shall comply with the requirements of Section 3.8. where,

- (a) new interior walls or floor assemblies are installed,
- (b) the *suite* has an area greater than 300 m², and
- (c) the *suite* is located in,
 - (i) a *floor area* where the existing difference in elevation between the adjacent ground level and the floor level is not more than 200 mm, or
 - (ii) a normally occupied *floor area* which is accessible by a passenger type elevator or other platform equipped passenger elevating device from an entrance *storey* where the existing difference in elevation between the adjacent ground level and the entrance *storey* level is not more than 200 mm.

(3) Except as provided in Section 11.5., the proposed *construction* within an existing *suite* shall comply with the requirements of Sentences 3.8.1.3.(6), 3.8.2.3.(6), 3.8.3.1.(6), 3.8.3.3.(19), 3.8.3.7.(1), 3.8.3.15.(5) and 3.8.3.16.(4) where new interior walls or floor assemblies are installed and only one of the following requirements is met:

- (a) the *suite* has an area greater than 300 m², or
- (b) the *suite* is located in a *floor area* described in Subclause (2)(c)(i) or in a normally occupied *floor area* described in Subclause (2)(c)(ii).

(4) Except as provided in Sentence (5), where existing interior walls or ceilings or floor assemblies or roof assemblies are substantially removed on any *storey* in an existing *building* and new interior walls, ceilings, floor assemblies or roof assemblies are installed, the *storey* shall be *sprinklered* if,

- (a) the *storey* will contain a Group C *major occupancy*, and
- (b) the *building* is over 3 *storeys* in *building height*.

(5) Sentence (4) does not apply where the *building*,

- (a) conforms to Subclause 3.2.2.44.(1)(a)(ii), and
- (b) contains *dwelling units* having *means of egress* conforming to Sentence 3.3.4.4.(8).

(6) Where existing interior walls or ceilings or floor assemblies or roof assemblies are substantially removed and new interior walls, ceilings, floor assemblies or roof assemblies are installed in an existing *building* or part of an existing *building* that is a retirement home regulated under the *Retirement Homes Act, 2010*, the following requirements apply:

- (a) the retirement home shall be *sprinklered*,
- (b) a voice communication system conforming to Article 3.2.4.23. shall be provided in the *building*, if Clause 3.2.6.8.(1) (b) or (c), as applicable, requires that such a voice communication system be provided in the *building*, and
- (c) doors to *suites* and sleeping rooms not within *suites* in the retirement home, other than doors leading directly to the exterior, shall be equipped with self-closing devices.

38. Items 70 to 76 of Table 11.5.1.1.A. of Division B of the Regulation are revoked and the following substituted:

70.	A70	3.8.1.2.	Existing accessible entrance acceptable. (See C.A. A74) Existing curb ramp conforming to Sentence 3.8.3.2.(3) is acceptable. Existing principal entrance acceptable, provided at least one <i>barrier-free</i> entrance is available.
71.	A71	3.8.1.3.(1)	Existing unobstructed width of 920 mm minimum is acceptable.
72.	A72	3.8.1.3.(4)	Existing unobstructed space not less than 1 500 mm in width and 1 500 mm in length located not more than 30 m apart is acceptable.
72.1	A72.1	3.8.3.2.(3)(b)	Existing curb ramp acceptable, provided width not less than 1 200 mm.
73.	A73	3.8.3.3.(1)	Existing doorway acceptable, provided not less than 810 mm wide.
73.1	A73.1	3.8.3.3.(11)(a)	Existing distance acceptable, provided not less than 1 200 mm plus the width of any door that swings into the space in the path of travel.
74.	A74	3.8.3.4.(1)(a)	Existing ramp acceptable, provided not less than 870 mm between handrails.
75.	A75	3.8.3.8.(5)	Existing grab bar is acceptable.
75.1	A75.1	3.8.3.12.	Existing universal washroom acceptable.
76.	A76	3.8.3.13.(2)(f)	Existing grab bar is acceptable.

76.1	A76.1	3.8.3.16.	Existing drinking fountain conforming to Clauses 3.8.3.16.(2)(a) and (b) acceptable.
76.2	A76.2	3.11.3.1.(9)	Existing clear width acceptable, provided not less than 900 mm.
76.3	A76.3	3.11.3.1.(14)	Existing painted line acceptable.

39. Items 71 to 77 of Table 11.5.1.1.B. of Division B of the Regulation are revoked and the following substituted:

71.	B71	3.8.1.2.	Existing accessible entrance acceptable. (See C.A. B75) Existing curb ramp conforming to Sentence 3.8.3.2.(3) is acceptable. Existing principal entrance acceptable, provided at least one <i>barrier-free</i> entrance is available.
72.	B72	3.8.1.3.(1)	Existing unobstructed width of 920 mm minimum is acceptable.
73.	B73	3.8.1.3.(4)	Existing unobstructed space not less than 1 500 mm in width and 1 500 mm in length located not more than 30 m apart is acceptable.
73.1	B73.1	3.8.3.2.(3)(b)	Existing curb ramp acceptable, provided width not less than 1 200 mm.
74.	B74	3.8.3.3.(1)	Existing doorway acceptable, provided not less than 810 mm wide.
74.1	B74.1	3.8.3.3.(11)(a)	Existing distance acceptable, provided not less than 1 200 mm plus the width of any door that swings into the space in the path of travel.
75.	B75	3.8.3.4.(1)(a)	Existing ramp acceptable, provided not less than 870 mm between handrails.
76.	B76	3.8.3.8.(5)	Existing grab bar is acceptable.
76.1	B76.1	3.8.3.12.	Existing universal washroom acceptable.
77.	B77	3.8.3.13.(2)(f)	Existing grab bar is acceptable.
77.1	B77.1	3.8.3.16.	Existing drinking fountain conforming to Clauses 3.8.3.16.(2)(a) and (b) acceptable.
77.2	B77.2	3.11.3.1.(9)	Existing clear width acceptable, provided not less than 900 mm.
77.3	B77.3	3.11.3.1.(14)	Existing painted line acceptable.

40. Items 81 to 87 of Table 11.5.1.1.C. of Division B of the Regulation are revoked and the following substituted:

81.	C81	3.8.1.2.	Existing accessible entrance acceptable. (see C.A. C85) Existing curb ramp conforming to Sentence 3.8.3.2.(3) is acceptable. Existing principal entrance acceptable, provided at least one <i>barrier-free</i> entrance is available.
82.	C82	3.8.1.3.(1)	Existing unobstructed width of 920 mm minimum is acceptable.
83.	C83	3.8.1.3.(4)	Existing unobstructed space not less than 1 500 mm in width and 1 500 mm in length located not more than 30 m apart is acceptable.
83.1	C83.1	3.8.3.2.(3)(b)	Existing curb ramp acceptable, provided width not less than 1 200 mm.
84.	C84	3.8.3.3.(1)	Existing doorway acceptable, provided not less than 810 mm wide.
84.1	C84.1	3.8.3.3.(11)(a)	Existing distance acceptable, provided not less than 1 200 mm plus the width of any door that swings into the space in the path of travel.
85.	C85	3.8.3.4.(1)(a)	Existing ramp acceptable, provided not less than 870 mm between handrails.
86.	C86	3.8.3.8.(5)	Existing grab bar is acceptable.
86.1	C86.1	3.8.3.12.	Existing universal washroom acceptable.
87.	C87	3.8.3.13.(2)(f)	Existing grab bar is acceptable.
87.1	C87.1	3.8.3.16.	Existing drinking fountain conforming to Clauses 3.8.3.16.(2)(a) and (b) acceptable.
87.2	C87.2	3.11.3.1.(9)	Existing clear width acceptable, provided not less than 900 mm.
87.3	C87.3	3.11.3.1.(14)	Existing painted line acceptable.

41. Items 74 to 80 of Table 11.5.1.1.D/E. of Division B of the Regulation are revoked and the following substituted:

74.	DE74	3.8.1.2.	Existing accessible entrance acceptable. (See C.A. DE78) Existing curb ramp conforming to Sentence 3.8.3.2.(3) is acceptable. Existing principal entrance acceptable, provided at least one <i>barrier-free</i> entrance is available.
75.	DE75	3.8.1.3.(1)	Existing unobstructed width of 920 mm minimum is acceptable.
76.	DE76	3.8.1.3.(4)	Existing unobstructed space not less than 1 500 mm in width and 1 500 mm in length located not more than 30 m apart is acceptable.
76.1	DE76.1	3.8.3.2.(3)(b)	Existing curb ramp acceptable, provided width not less than 1 200 mm.
77.	DE77	3.8.3.3.(1)	Existing doorway acceptable, provided not less than 810 mm wide.
77.1	DE77.1	3.8.3.3.(11)(a)	Existing distance acceptable, provided not less than 1 200 mm plus the width of any door that swings into the space in the path of travel.
78.	DE78	3.8.3.4.(1)(a)	Existing ramp acceptable, provided not less than 870 mm between handrails.
79.	DE79	3.8.3.8.(5)	Existing grab bar is acceptable.
79.1	DE79.1	3.8.3.12.	Existing universal washroom acceptable.
80.	DE80	3.8.3.13.(2)(f)	Existing grab bar is acceptable.

80.1	DE80.1	3.8.3.16.	Existing drinking fountain conforming to Clauses 3.8.3.16.(2)(a) and (b) acceptable.
------	--------	-----------	--

42. Items 75 to 81 of Table 11.5.1.1.F. of Division B of the Regulation are revoked and the following substituted:

75.	F75	3.8.1.2.	Existing accessible entrance acceptable. (See <i>C.A. F79</i>)
			Existing curb ramp conforming to Sentence 3.8.3.2.(3) is acceptable. Existing principal entrance acceptable, provided at least one <i>barrier-free</i> entrance is available.
76.	F76	3.8.1.3.(1)	Existing unobstructed width of 920 mm minimum is acceptable.
77.	F77	3.8.1.3.(4)	Existing unobstructed space not less than 1 500 mm in width and 1 500 mm in length located not more than 30 m apart is acceptable.
77.1	F77.1	3.8.3.2.(3)(b)	Existing curb ramp acceptable, provided width not less than 1 200 mm.
78	F78	3.8.3.3.(1)	Existing doorway acceptable, provided not less than 810 mm wide.
78.1	F78.1	3.8.3.3.(11)(a)	Existing distance acceptable, provided not less than 1 200 mm plus the width of any door that swings into the space in the path of travel.
79.	F79	3.8.3.4.(1)(a)	Existing ramp acceptable, provided not less than 870 mm between handrails.
80.	F80	3.8.3.8.(5)	Existing grab bar is acceptable.
80.1	F80.1	3.8.3.12.	Existing universal washroom acceptable.
81.	F81	3.8.3.13.(2)(f)	Existing grab bar is acceptable.
81.1	F81.1	3.8.3.16.	Existing drinking fountain conforming to Clauses 3.8.3.16.(2)(a) and (b) acceptable.

Commencement

43. This Regulation comes into force on January 1, 2015.

2/14

NOTE: Consolidated regulations and various legislative tables pertaining to regulations can be found on the e-Laws website (www.e-Laws.gov.on.ca).

REMARQUE : Les règlements codifiés et diverses tables concernant les règlements se trouvent sur le site Lois-en-ligne (www.lois-en-ligne.gouv.on.ca).

This page intentionally left blank
Cette page est volontairement laissée en blanc

INDEX 02

Government Notices Respecting Corporations.....	113
Avis du gouvernements relatifs aux compagnies	113
Notice of Default in Complying with the Corporations Tax Act	113
Avis de non-observation de la Loi sur l'imposition des sociétés	113
Cancellation of Certificate of Incorporation (Corporations Tax Act Defaulters).....	114
Annulation de certificat de constitution (Non-observation de la Loi sur l'imposition des sociétés)	114
Certificate of Dissolution.....	115
Certificat de dissolution.....	115
Erratum Notice.....	116
Avis d'erreur	116
Notice of Determination of Residual Stranded Debt for March 31, 2013, under O. Reg. 89/12	117
Avis de détermination du reliquat de la dette insurmontable en date du 31 mars 2013, en vertu du Règl. de l'Ont. 89/12	117
Applications to Provincial Parliament — Private Bills	117
Demandes au Parlement provincial — Projets de loi d'intérêt privé.....	117
Applications to Provincial Parliament	117
Demandes au Parlement provincial.....	117
 SALE OF LAND FOR TAX ARREARS BY PUBLIC TENDER	
VENTES DE TERRAINS PAR APPEL D'OFFRES POUR ARRIÉRÉ D'IMPÔT	117
THE CORPORATION OF THE TOWN OF BLIND RIVER	117
THE CORPORATION OF THE TOWNSHIP OF MADOC	119
THE CORPORATION OF THE TOWNSHIP OF CONMEE	119
 PUBLICATIONS UNDER PART III (REGULATIONS) OF THE LEGISLATION ACT, 2006	
RÈGLEMENTS PUBLIÉS EN APPLICATION DE LA PARTIE III (RÈGLEMENTS) DE LA LOI DE 2006 SUR LA LÉGISLATION	121
BUILDING CODE ACT, 1992	O. Reg. 368/13.....123
DEVELOPMENT CORPORATIONS ACT	O. Reg. 366/13.....121
PERSONAL HEALTH INFORMATION PROTECTION ACT, 2004	O. Reg. 367/13.....122
 Texte d'information pour la gazette de l'Ontario.....	149
 Information Text for Ontario Gazette	150

This page intentionally left blank
Cette page est volontairement laissée en blanc

This page intentionally left blank
Cette page est volontairement laissée en blanc

This page intentionally left blank
Cette page est volontairement laissée en blanc



Texte d'information pour la gazette de l'Ontario

La Gazette de l'Ontario paraît chaque samedi, et les annonces à y insérer doivent parvenir à ses bureaux le jeudi à 15h au plus tard, soit au moins neuf jours avant la parution du numéro dans lequel elles figureront. Pour les semaines incluant le lundi de Pâques, le 11 novembre et les congés statutaires, accordez une journée de surplus. Pour connaître l'horaire entre Noël et le Jour de l'An s'il vous plaît communiquez avec le bureau de La Gazette de l'Ontario au (416) 326-5310 ou par courriel à mbs.GazettePubsOnt@ontario.ca

Tarifs publicitaires et soumission de format:

- 1) Envoyer les annonces dans le format **Word.doc** par courriel à mbs.GazettePubsOnt@ontario.ca
- 2) Le tarif publicitaire pour la première insertion envoyée électroniquement est de 75,00\$ par espace-colonne jusqu'à un ¼ de page.
- 3) Pour chaque insertion supplémentaire commandée en même temps que l'insertion initiale, le tarif est 40,00\$
- 4) Les clients peuvent confirmer la publication d'une annonce en visitant le site web de La Gazette de l'Ontario www.ontariogazette.gov.on.ca ou en visionnant une copie imprimée à une bibliothèque locale.

Abonnement:

Le tarif d'abonnement annuel est de 126,50\$ + T.V.H. pour 52 ou 53 numéros hebdomadaires débutant le premier samedi du mois de janvier (payable à l'avance) L'inscription d'un nouvel abonnement au courant de l'année sera calculée de façon proportionnelle pour la première année. Un nouvel abonné peut commander des copies d'éditions précédentes de la Gazette au coût d'une copie individuelle si l'inventaire le permet.

Le remboursement pour l'annulation d'abonnement sera calculé de façon proportionnelle à partir de 50% ou moins selon la date. Pour obtenir de l'information sur l'abonnement ou les commandes s.v.p. téléphonez le (416) 326-5306 durant les heures de bureau.

Copies individuelles:

Des copies individuelles de la Gazette peuvent être commandées en direct en ligne au site www.serviceontario.ca/publications ou en téléphonant 1-800-668-9938.

Options de paiement:

Les paiements peuvent être effectués au moyen de la carte Visa, MasterCard ou Amex, ou chèques ou mandats fait à l'ordre du MINISTRE DES FINANCES. Toute correspondance, notamment les changements d'adresse, doit être adressée à :

LA GAZETTE DE L'ONTARIO

700, avenue University, 6e étage, Toronto, Ontario M74 2S4

Téléphone (416) 326-5306

Paie ment – Annonces:

Pour le traitement rapide les clients peuvent faire leur paiement au moyen de la carte Visa, MasterCard ou Amex lorsqu'ils soumettent leurs annonces. Les frais peuvent également être facturés.

MINISTÈRES DU GOUVERNEMENT DE L'ONTARIO S.V.P. NOTEZ

Paiements par écriture de journal seulement. S.V.P. communiquez avec le bureau de la Gazette au 416 326-5310 ou à mbs.GazettePubsOnt@ontario.ca



Information Text for Ontario Gazette

The Ontario Gazette is published every Saturday. Advertisements/notices must be received no later than 3 pm on Thursday, 9 days before publication of the issue in which they should appear. For weeks including Easter Monday, November 11th or a statutory holiday allow an extra day. For the Christmas/New Year holiday schedule please contact the Gazette at (416) 326-5310 or by email at mbs.GazettePubsOnt@ontario.ca

Advertising rates and submission formats:

- 1) Please submit all notices in a **Word.doc** format to: mbs.GazettePubsOnt@ontario.ca
- 2) For a first insertion electronically submitted the basic rate is \$75 up to ¼ page.
- 3) For subsequent insertions of the same notice ordered at the same time the rate is \$40 each.
- 4) Clients may confirm publication of a notice by visiting The Ontario Gazette web site at: www.ontariogazette.gov.on.ca or by viewing a printed copy at a local library.

Subscriptions:

The annual subscription rate is \$126.50 + H.S.T. for 52 or 53 weekly issues beginning the first Saturday in January, payable in advance. In-year new subscriptions will be pro-rated for the first year. A new subscriber may order back issues of the Gazette at the single-copy rate as inventory permits.

Refunds for cancelled subscriptions will be pro-rated from 50% or less depending upon date. For subscription information/orders please call (416) 326-5306 during normal business hours.

Single Copies:

Individual Gazette copies may be ordered on-line through the website at www.serviceontario.ca/publications or by phone at 1-800-668-9938.

Payment Options:

Subscriptions may be paid by VISA, AMEX or MasterCard or by Cheque or Money order payable to THE MINISTER OF FINANCE. All subscription enquiries and correspondence, including address changes, should be mailed to:

THE ONTARIO GAZETTE

700 University Avenue, 6th Floor, Toronto, Ontario M7A 2S4

Telephone: (416) 326-5306

Payment – Notices:

For fastest processing clients may pay by VISA, AMEX or MasterCard when submitting notices. Charges may also be invoiced.

ONTARIO GOVERNMENT MINISTRIES PLEASE NOTE:

Payment by Journal Entry only. Please contact the Gazette office at 416 326-5310 or at mbs.GazettePubsOnt@ontario.ca

